

PRODUCT-DETAILS

1095 U-500

1095 U-500 Inserts



General Information

| | |
|-----------------------|--|
| Extended Product Type | 1095 U-500 |
| Product ID | 2CKA001032A0514 |
| EAN | 4011395176252 |
| Catalog Description | 1095 U-500 Inserts |
| Long Description | With built-in slide switch and control lamp for nightly reduction of 4 K. Switch contact opens when the set temperature is reached. With fixing claws. Separate terminal to activate nighttime mode and reduction of room temperature by 4K. Class of temperature controller 1 Contribution to space heating energy efficiency 1,0%. |

Technical

| | |
|--------------|--|
| Suitable For | 2CKA001710A3534 2CKA001710A3546 2CKA001710A3548 2CKA001710A3542 2CKA001710A3540 2CKA001710A3550 2CKA001710A3554 2CKA001710A3552 2CKA001710A3535 2CKA001710A3533 2CKA001710A3532 2CKA001710A3531 2CKA001710A3530 2CKA001710A3553 2CKA001710A3551 2CKA001710A3629 2CKA001710A3538 2CKA001710A3536 |
|--------------|--|

2CKA001710A3549
 2CKA001710A3539
 2CKA001710A3541
 2CKA001710A3547
 2CKA001710A3545
 2CKA001710A3544
 2CKA001710A3537
 2CKA001710A3543
 2CKA001710A3755
 2CKA001710A3668
 2CKA001710A3744
 2CKA001710A3745
 2CKA001710A3816
 2CKA001710A3847
 2CKA001710A3827
 2CKA001710A4062

| | |
|---------------------------------|--|
| Rated Voltage (U _r) | 230 V |
| Auxiliary Voltage AC/DC | 230 V AC/DC |
| Rated Current (I _n) | 10 A |
| Operating Mode | Turn |
| Product Range | Flush-mounted installation boxes and inserts |
| Connection Type | Three-Four Wired |
| Mounting Type | Flush Mounted |
| Sensor Type | Resistance sensor |
| Model Number | On/Off |
| Battery Weight | 0 g |
| Number of Batteries | 0 |

Environmental

| | |
|---------------------------|---|
| Ambient Air Temperature | Operation 5 ... +30 °C |
| Degree of Protection | IP20 |
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Temperature Class Default | I |
| SCIP | c188ac42-24c8-4dd0-9bb1-8e9cc2c6b498 Germany (DE) |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 52 mm |
| Product Net Height | 12 mm |
| Product Net Depth / Length | 32 mm |
| Product Net Weight | 0.12 kg |

Container Information

| | |
|--------------------------------|-----------------|
| Package Level 1 Units | carton 1 piece |
| Package Level 1 Width | 92 mm |
| Package Level 1 Height | 58 mm |
| Package Level 1 Depth / Length | 78 mm |
| Package Level 1 Gross Weight | 0.12 kg |
| Package Level 1 EAN | 4011395176252 |
| Package Level 2 Units | carton 10 piece |
| Package Level 2 Width | 168 mm |
| Package Level 2 Height | 112 mm |
| Package Level 2 Depth / Length | 298 mm |

Package Level 2 Gross
Weight

1.375 kg

Ordering

| | |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 90321020 |
| Country of Origin | Germany (DE) |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|--|
| Declaration of Conformity - CE | 2CKA100000E0140 |
| Instructions and Manuals | DEBJE-1094-1097_BJE_OA_2012-12-17_DE_R01 |
| REACH Declaration | 2CKA309999E9999 |
| RoHS Information | 9AKK104295D8727 |

Popular Downloads

| | |
|-----------------------------------|--|
| Data Sheet, Technical Information | No document needed |
| Instructions and Manuals | DEBJE-1094-1097_BJE_OA_2012-12-17_DE_R01 |

Classifications

| | |
|----------------|--|
| ETIM 7 | EC010927 - Room thermostat |
| ETIM 8 | EC010927 - Room thermostat |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 9032 10 20 |
| eClass | V11.0 : 27210712 |

Categories

Low Voltage Products and Systems → Switch Assortments → Inserts → Control

