



Fuse-link, high speed, 25 A, AC 600 V, 200 kA, 10 x 38 mm, aR, UL

Part no. 25AMP 600V AC FERRULE 10 X 38MM
Catalog No. FWC-25A10F

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	25
Rated voltage			AC 600 V
Size			10 x 38 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL 248
Optional accessories			fuse-holder CHM1DU

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecI@ss10.0.1-27-14-20-01 [AFZ796015])			
Model			Ceramic fuse
Size			10x38 mm
Voltage type			AC/DC
Rated current		A	25
Rated voltage		V	600
Utilization category			aR (accompanied semiconductor protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	200
Power loss at rated current		W	6