



Fuse-link, high speed, 30 A, AC 700 V, 14 x 51 mm, aR, UL

FWP-30A14F

Similar to illustration

General specifications		
Product name		Eaton Bussmann series high speed cylindrical fuse
Part no.		FWP-30A14F
EAN		5027590500579
Product Length/Depth		51 millimetre
Product height		15 millimetre
Product width		15 millimetre
Product weight		20.3 gram
Compliances		RoHS Compliant CE Marked
Certifications		CSA Certified UL Recognized
Product Tradename		None
Product Type		High speed cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		30 A
Voltage rating		700 V
Voltage type		AC/DC
Interrupt rating		200 kAIC
Class		Class aR
Clearing (I2T)		400
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator		Non Indicating
Fuse size		14 x 51 mm
Quantity		10
Compatible microswitch		
Accessories		CH14 Modular fuse holder FW14-PCB

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ec1@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		14x51 mm
Voltage type		AC/DC
Rated current	A	30
Rated voltage	V	700
Utilization category		aR (accompanied semiconductor protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	200
Power loss at rated current	W	9