



High speed square body fuse

170M2669

| General specifications      |  |  |
|-----------------------------|--|--|
| Product name                |  | Eaton Bussmann series high speed square body fuse                    |
| Part no.                    |  | 170M2669   |
| EAN                         |  | 5027590442466  |
| Product Length/Depth        |  | 98 millimetre  |
| Product height              |  | 51 millimetre  |
| Product width               |  | 28 millimetre  |
| Product weight              |  | 211.833 gram   |
| Compliances                 |  | RoHS Compliant<br>CE Marked  |
| Certifications              |  | IEC Rated<br>UL Recognized   |
| Product Tradename           |  | None   |
| Product Type                |  | High speed square body fuse  |
| Product Sub Type            |  | None   |
| Electrical data             |  |  |
| Amperage Rating             |  | 315 A  |
| Voltage rating              |  | 690 V (IEC), 700 V (UL)  |
| Interrupt rating            |  | 200 kAIC   |
| Class                       |  | Class aR   |
| Clearing (I <sub>2</sub> T) |  | 68500 at 660 V   |
| Product specifications      |  |  |
| Application                 |  | Semiconductor, DC Common bus, DC drives, power converters/rectifiers |
| Fuse type                   |  | DIN 43653<br>TN/80 Type T Indicator for Micro                        |
| Fuse indicator              |  | Other  |
| Fuse size                   |  | 00   |