



Fuse-link, low voltage, 63 A, AC 690 V, 80 kA, 22 x 58 mm, gL/gG, IEC

Part no.	CYLINDRICAL FUSE 22 x 58 63A GG 690V AC
Catalog No.	C22G63
EL-Nummer (Norway)	1664187

Delivery program

Product range		Fuse
Basic function		Fuse-link
Field of application		low voltage
Rated current	I	A
Rated voltage		63
Size		AC 690 V
Utilization category		22 x 58 mm
Breaking Capacity		gL/gG
usable for size/applications		80
Standard/Approval		for industrial applications
Shape		for general purpose use
Standards/Regulations		IEC
		cylindrical
		IEC 60269-2

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])

Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	63
Rated voltage	V	690
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	6.9