

**Fuse holder, low voltage, 32 A, DC 1000 V, 10 x 38 mm, gPV, 2P, UL, IEC, with indicator**



**Part no.** 2P 10x38MFH30A1000Vdc gPV with indicator  
**Catalog No.** CHPV2IU

**EL-Nummer** 4300322  
**(Norway)**

## Delivery program

Product range			Fuse accessory
Basic function			Fuse-holder
Field of application			low voltage
Rated current	I	A	32
Rated voltage			DC 1000 V
Size			10 x 38 mm
Utilization category			gPV
Status indicator			with indicator
Description			DIN rail mounting colour-coded Rated for use with 75°C or 90°C wire fine stranded wire spade terminals and with comb-bus bars Use any higher temperature rated wire with appropriate derating. Modular
Number of poles			2P
usable for size/applications			Photovoltaic for cylindrical fuse-links
Standard/Approval			UL IEC
Standards/Regulations			IEC cULus CCC CSA UR

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)	
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss8.1-27-14-21-21 [ADI305004])	
For fuse size	10x38 mm
Number of poles	2
Concurrently switching N-neutral	No