



SIRIUS safety relay Basic unit Standard series Relay enabling circuits 3 NO contacts plus Relay signaling circuit 1 NC contact Us = 24 V AC/DC Spring-type terminal (push-in)

product brand name	SIRIUS
product category	Safety relays
product designation	safety relays
design of the product	Relay enabling circuits
General technical data	
protection class IP of the enclosure	IP20
touch protection against electrical shock	finger-safe
insulation voltage rated value	300 V
ambient temperature	<ul style="list-style-type: none">• during storage -40 ... +80 °C• during operation -25 ... +60 °C
air pressure according to SN 31205	90 ... 106 kPa
relative humidity during operation	10 ... 95 %
installation altitude at height above sea level maximum	4 000 m; Derating, see Product Notification 109792701
vibration resistance according to IEC 60068-2-6	5 ... 500 Hz: 0.75 mm
shock resistance	10g / 11 ms
surge voltage resistance rated value	4 000 V
EMC emitted interference	IEC 60947-5-1, IEC 61000
installation environment regarding EMC	This product is suitable for Class B environments and can also be used in domestic environments.
overvoltage category	3
degree of pollution	3
reference code according to IEC 81346-2	F
power loss [W] maximum	2 W
number of sensor inputs 1-channel or 2-channel	1
design of the cascading	none
type of the safety-related wiring of the inputs	single-channel and two-channel
product feature cross-circuit-proof	Yes
Safety Integrity Level (SIL)	
• according to IEC 62061	3
• according to IEC 61508	3
performance level (PL)	
• according to ISO 13849-1	e
category according to EN ISO 13849-1	4
Safe failure fraction (SFF)	99 %
PFHD with high demand rate according to EN 62061	1.7E-9 1/h
PFDavg with low demand rate according to IEC 61508	1E-6
T1 value for proof test interval or service life according to IEC 61508	20 a
hardware fault tolerance according to IEC 61508	1
safety device type according to IEC 61508-2	Type A

Inputs/ Outputs	
number of outputs as contact-affected switching element	
• as NC contact	1
— for signaling function instantaneous contact	
• as NO contact	3
— safety-related instantaneous contact	0
— safety-related delayed switching	0
stop category according to EN 60204-1	0
design of input	
• cascading input/functional switching	No
• feedback input	Yes
• start input	Yes
type of electrical connection plug-in socket	No
operating frequency maximum	360 1/h
switching capacity current	
• of the NO contacts of the relay outputs	
— at DC-13	
— at 24 V	5 A
— at 115 V	0.2 A
— at 230 V	0.1 A
— at AC-15	
— at 115 V	5 A
— at 230 V	5 A
• of the NC contacts of the relay outputs	
— at DC-13	
— at 24 V	1 A
— at 115 V	0.2 A
— at 230 V	0.1 A
— at AC-15	
— at 115 V	1.5 A
— at 230 V	1.5 A
thermal current of the switching element with contacts maximum	5 A
total current maximum	12 A
operational current at 17 V minimum	5 mA
mechanical service life (operating cycles) typical	10 000 000
design of the fuse link for short-circuit protection of the NO contacts of the relay outputs required	gL/gG: 6A or circuit breaker type A: 3A or circuit breaker type B: 2A or circuit breaker type C: 1A
design of the fuse link for short circuit protection of the NC contacts of the relay outputs required	Diazed or Neozed fuses, operating class gL/gG: 6 A or MCB type A: 2 A or MCB type B: 2 A or MCB type C: 1 A
wire length	
• for total of all sensor circuits with Cu 1.5 mm ² and 150 nF/km maximum	2 000 m
make time with automatic start	
• typical	200 ms
• at DC maximum	320 ms
• at AC maximum	320 ms
make time with automatic start after power failure	
• typical	200 ms
• maximum	320 ms
make time with monitored start	
• maximum	20 ms
• typical	15 ms
backslide delay time after opening of the safety circuits typical	10 ms
backslide delay time in the event of power failure	
• typical	65 ms
• maximum	75 ms
recovery time after opening of the safety circuits typical	10 ms
recovery time after power failure typical	0.09 s
pulse duration	
• of the sensor input minimum	150 ms
• of the ON pushbutton input minimum	0.015 s

Control circuit/ Control							
type of voltage of the control supply voltage	AC/DC						
control supply voltage frequency							
• 1 rated value	50 Hz						
• 2 rated value	60 Hz						
control supply voltage							
• at DC							
— rated value	24 V						
• at AC							
— at 50 Hz	24 V						
— rated value							
— at 60 Hz	24 V						
— rated value							
operating range factor control supply voltage rated value of magnet coil							
• at AC							
— at 50 Hz	0.85 ... 1.1						
— at 60 Hz	0.85 ... 1.1						
• at DC	0.85 ... 1.2						
Installation/ mounting/ dimensions							
mounting position	any						
required spacing for grounded parts at the side	5 mm						
fastening method	screw and snap-on mounting						
width	22.5 mm						
height	100 mm						
depth	121.6 mm						
Connections/ Terminals							
type of electrical connection	spring-loaded terminal (push-in)						
type of connectable conductor cross-sections							
• solid	1x (0.5 ... 1.5 mm ²), 2x (0.5 ... 1.5 mm ²)						
• finely stranded							
— with core end processing	1x (0.5 ... 1.0 mm ²), 2x (0.5 ... 1.0 mm ²)						
— without core end processing	1x (0.5 ... 1.5 mm ²), 2x (0.5 ... 1.5 mm ²)						
type of connectable conductor cross-sections at AWG cables							
• solid	1x (20 ... 16), 2x (20 ... 16)						
• stranded	1x (20 ... 16), 2x (20 ... 16)						
Product Function							
product function parameterizable	sensor floating / sensor non-floating, monitored start-up / automatic start						
suitability for operation device connector 3ZY12	No						
suitability for interaction press control	No						
suitability for use							
• safety switch	Yes						
• monitoring of floating sensors	Yes						
• monitoring of non-floating sensors	Yes						
• magnetically operated switch monitoring	Yes						
• safety-related circuits	Yes						
Certificates/ approvals							
General Product Approval							
EMC							
 CSA	 CCC	Confirmation	 UL	 EAC	 RCM		
Functional Safety/Safety of Machinery		Declaration of Conformity		Test Certificates		Marine / Shipping	

Marine / Shipping

other

Railway



[Confirmation](#)

[Confirmation](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SK1111-2AB30>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SK1111-2AB30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SK1111-2AB30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SK1111-2AB30&lang=en



