



INSTA contactor with 4 NO contacts Contact for 230 V AC, 400V 25A
Control 24 V AC

Model	
product brand name	SETRON
product designation	Insta contactor
design of the product	4 NO contacts
type of voltage of the operating voltage	AC
type of voltage of the operating voltage for actuation	AC
Supply voltage	
operating voltage rated value	
• minimum	440 V
• maximum	440 V
Protection class	
protection class IP	IP20
Switching capacity	
switching capacity active power with incandescent lamp load	2 000 W
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	2.2 W
Control current	
control supply voltage	
• rated value	24 V
• rated value maximum	24 V
Product details	
product component slide for manual operation	No
number of NC contacts	0
number of NO contacts	4
product extension installable supplementary devices	Yes
Connections	
installation or assembly note	provision must be made for spacers to ensure heat dissipation
Mechanical Design	
height	90 mm
width	36 mm
depth	71 mm
installation depth	0 mm
number of modular width units	2
net weight	272 g
General Product Approval	
Declaration of Conformity	



Declaration of Conformity	Test Certificates	other	Environment
---------------------------	-------------------	-------	-------------



Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT5830-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT5830-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT5830-2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/30/2022 

