



SITOP PSU100C/1ACDC/24VDC/4A

SITOP PSU100C 24 V/4 A stabilized power supply input: 120-230 V AC (110-300 V DC) output: 24 V DC/4 A \*Ex approval no longer available\*

| Input  |   |
|--|---|
| type of the power supply network   | 1-phase AC or DC  |
| supply voltage at AC   |   |
| • minimum rated value  | 100 V   |
| • maximum rated value  | 230 V   |
| • initial value  | 85 V  |
| • full-scale value   | 264 V   |
| input voltage  |   |
| • at DC  | 110 ... 300 V   |
| design of input wide range input   | Yes   |
| overvoltage overload capability  | 2.3 × Vin rated, 1.3 ms   |
| operating condition of the mains buffering   | at Vin = 230 V  |
| buffering time for rated value of the output current in the event of power failure minimum | 20 ms   |
| operating condition of the mains buffering   | at Vin = 230 V  |
| line frequency   |   |
| • 1 rated value  | 50 Hz   |
| • 2 rated value  | 60 Hz   |
| line frequency   | 47 ... 63 Hz  |
| input current  |   |
| • at rated input voltage 100 V   | 2.25 A  |
| • at rated input voltage 230 V   | 1.15 A  |
| current limitation of inrush current at 25 °C maximum                                      | 34 A  |
| I2t value maximum  | 3 A²·s  |
| fuse protection type   | internal  |
| • in the feeder  | Recommended miniature circuit breaker: from 16 A characteristic B or from 10 A characteristic C |
| Output   |   |
| voltage curve at output  | Controlled, isolated DC voltage   |
| output voltage at DC rated value   | 24 V  |
| output voltage   |   |
| • at output 1 at DC rated value  | 24 V  |
| relative overall tolerance of the voltage  | 3 %   |
| relative control precision of the output voltage   |   |
| • on slow fluctuation of input voltage   | 0.1 %   |
| • on slow fluctuation of ohm loading   | 0.2 %   |
| residual ripple  |   |
| • maximum  | 200 mV  |
| • typical  | 80 mV   |
| voltage peak   |   |
| • maximum  | 300 mV  |
| • typical  | 80 mV   |

|  |  |
|--|--|
| adjustable output voltage  | 22.2 ... 26.4 V  |
| product function output voltage adjustable                               | Yes  |
| type of output voltage setting   | via potentiometer  |
| display version for normal operation                                     | Green LED for output voltage OK                                      |
| behavior of the output voltage when switching on                         | Overshoot of Vout approx. 1 %  |
| response delay maximum   | 1.5 s  |
| voltage increase time of the output voltage                              |  |
| • typical  | 400 ms   |
| output current   |  |
| • rated value  | 4 A  |
| • rated range  | 0 ... 4 A; +55 ... +70 °C: Derating 3%/K; at +70 °C Iout rated 2.2 A |
| supplied active power typical  | 96 W   |
| product feature  |  |
| • bridging of equipment  | Yes; Start-up with single nominal load only                          |
| number of parallel-switched equipment resources for increasing the power | 2  |

### Efficiency

|   |        |
|---|--------|
| efficiency in percent   | 88 %   |
| power loss [W]  |        |
| • at rated output voltage for rated value of the output current typical | 13 W   |
| • during no-load operation maximum                                      | 0.75 W |

### Closed-loop control

|   |       |
|---|-------|
| relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical | 0.1 % |
| relative control precision of the output voltage at load step of resistive load 10/90/10 % typical              | 3 %   |
| setting time  |       |
| • load step 10 to 90% typical   | 4 ms  |
| • load step 90 to 10% typical   | 4 ms  |

### Protection and monitoring

|  |  |
|--|--|
| design of the overvoltage protection           | Yes, according to EN 60950-1           |
| • typical                                      | 4.8 A                                  |
| property of the output short-circuit proof     | Yes                                    |
| design of short-circuit protection             | Electronic shutdown, automatic restart |
| display version for overload and short circuit | -                                      |

### Safety

|   |  |
|---|--|
| galvanic isolation between input and output | Yes  |
| galvanic isolation                          | Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178 |
| operating resource protection class         | Class I  |
| leakage current                             |  |
| • maximum                                   | 3.5 mA   |
| • typical                                   | 0.4 mA   |
| protection class IP                         | IP20   |

### Approvals

|  |   |
|--|---|
| certificate of suitability                       |   |
| • CE marking                                     | Yes   |
| • UL approval                                    | Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1) |
| • CSA approval                                   | Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1) |
| • cCSAus, Class 1, Division 2                    | No  |
| • ATEX   | No  |
| certificate of suitability                       |   |
| • IECEx  | No  |
| • NEC Class 2                                    | No  |
| • ULhazloc approval                              | No  |
| • FM registration                                | No  |
| type of certification CB-certificate             | Yes   |
| certificate of suitability                       |   |
| • EAC approval                                   | Yes   |
| certificate of suitability shipbuilding approval | Yes   |
| shipbuilding approval                            | ABS, DNV GL   |
| Marine classification association                |   |

|   |     |
|---|-----|
| • American Bureau of Shipping Europe Ltd. (ABS) | Yes |
| • French marine classification society (BV)     | No  |
| • DNV GL  | Yes |
| • Lloyds Register of Shipping (LRS)             | No  |
| • Nippon Kaiji Kyokai (NK)                      | No  |

## EMC

|                                  |                  |
|----------------------------------|------------------|
| standard                         |                  |
| • for emitted interference       | EN 55022 Class B |
| • for mains harmonics limitation | EN 61000-3-2     |
| • for interference immunity      | EN 61000-6-2     |

## environmental conditions

|   |  |
|---|--|
| ambient temperature                           |  |
| • during operation                            | -20 ... +70 °C; with natural convection      |
| • during transport                            | -40 ... +85 °C                               |
| • during storage                              | -40 ... +85 °C                               |
| environmental category according to IEC 60721 | Climate class 3K3, 5 ... 95% no condensation |

## Mechanics

|  |  |
|--|--|
| type of electrical connection                            | screw-type terminals   |
| • at input   | L, N, PE: Removable screw terminal, each for 1 x 0.5 ... 2.5 mm <sup>2</sup>                               |
| • at output  | +: 1 screw terminal for 0.5 ... 2.5 mm <sup>2</sup> ; -: 2 screw terminals for 0.5 ... 2.5 mm <sup>2</sup> |
| • for auxiliary contacts                                 | -  |
| width of the enclosure                                   | 52.5 mm  |
| height of the enclosure                                  | 80 mm  |
| depth of the enclosure                                   | 100 mm   |
| required spacing   |  |
| • top  | 50 mm  |
| • bottom   | 50 mm  |
| • left   | 0 mm   |
| • right  | 0 mm   |
| net weight   | 0.32 kg  |
| product feature of the enclosure housing can be lined up | Yes  |
| fastening method   | Snaps onto DIN rail EN 60715 35x7.5/15   |
| electrical accessories                                   | Removable spring-type terminal 6EP1971-5BA00   |
| MTBF at 40 °C  | 2 726 727 h  |
| other information  | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)          |

