

Clamp terminal, 1000mm² for 30x10 and T profile

Part no. **AKS1000**
 Catalog No. **107208**



Delivery program

Product range			60 mm system 185 mm system
Basic function			Connections
Subrange			Clamp terminals
Description			Termination to busbars without drilling A contact block is used to connect the conductor to the busbar
Terminal area W x H		mm	55 x 28
Width		mm	72
Rated operational current	I _e	A	1600
conductor			up to # (2 x) 10 x 50 x 1 mm up to ■ (2x) 50 x 10 mm
Cu factor		kg	0,20
For use with			20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile
Notes			
○ round conductor, solid			
● Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
□ Section conductor, solid			
Sector conductor, stranded			
# CU band			
■ CU busbar			

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)	
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])	
Busbar thickness	mm 5 - 10
Busbar width	mm 20 - 30
Suitable for	Flat rail
Width clamp	mm 72
Max. conductor cross section	mm ² 1000
Max. rated operation current I _e	A 1600
Suitable for round conductor connection	Yes
Suitable for sector conductor connection	Yes
Suitable for strip conductor connection	Yes