



ALPHA 160, wall-mounted cabinet, Surface mounting, with distribution board panel, IP44, Protection class 2, H: 650 mm, W: 550 mm, T: 140 mm, RAL 9016

Model		
product brand name	ALPHA	
product designation	Wall-mounted cabinet	
design of the product	Surface mounting, with distribution board panel	
surface processing	powder-coated	
Protection class		
protection class IP	IP44	
operating resource protection class	Safety class 2	
IK protection class	IK08	
suitability for interaction lightning protection	Yes	
suitability for use for outside use	No	
Appearance		
RAL color number	9016	
product component		
• cable entry	Yes	
• mounting plate	No	
product extension optional side-by-side mounting	Yes	
number of DIN mounting bars	8	
number of rows	8	
Mechanical Design		
height	650 mm	
width	550 mm	
depth	140 mm	
installation depth	140 mm	
number of modular width units	96	
number of modular width units per DIN mounting bar	12	
fastening method	Aufputz	
net weight	12.18 kg	
material of the enclosure	Steel	
Approvals Certificates		
General Product Approval	Test Certificates	
 Confirmation	 Miscellaneous	
	 Special Test Certificate	
Test Certificates	other	Environment

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8GK1052-2KK21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8GK1052-2KK21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK1052-2KK21

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

8/29/2023

