



ALPHA 400, wall-mounted cabinet, Flat Pack, IP43, Protection class 1, H: 1250 mm, W: 800 mm, T: 210 mm, RAL 9016

Model	
product brand name	ALPHA
product designation	Wall-mounted cabinet
design of the product	Flat pack
surface processing	powder-coated
Protection class	
protection class IP	IP43
operating resource protection class	Safety class 1
IK protection class	IK09
suitability for interaction lightning protection	Yes
suitability for use for outside use	No
Appearance	
RAL color number	9016
product component	
• cable entry	Yes
• mounting plate	No
product extension optional side-by-side mounting	Yes
number of rows	24
Mechanical Design	
height	1 250 mm
width	800 mm
depth	210 mm
installation depth	210 mm
number of modular width units	288
number of modular width units per DIN mounting bar	12
fastening method	Aufputz
net weight	29 kg
material of the enclosure	Steel

Approvals Certificates

General Product Approval

[Confirmation](#)



[Miscellaneous](#)



Test Certificates	other	Environment
-------------------	-------	-------------

[Type Test Certific-](#)
[Special Test Certific-](#)
[Miscellaneous](#)
[Confirmation](#)
[Environmental Con-](#)
[Environmental Con-](#)

Further information**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8GK1102-6KK32>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8GK1102-6KK32>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK1102-6KK32

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

8/29/2023 

