

ALPHA copper busbar 250 A 12 x 5 mm, 250 A, W = 500



Model	
product brand name	ALPHA
product designation	CU busbar
design of the product	12x5 mm, 250 A, W=500
busbar design	others
General technical data	
surface processing tin-plated	No
Main circuit	
operational current rated value	250 A
Product details	
product feature flexible	No
Mechanical Design	
width	12 mm
length	491 mm
thickness of busbar	5 mm
material of the busbar	Cu
Approvals Certificates	
General Product Approval	



[Confirmation](#)



[Miscellaneous](#)



Test Certificates	other	Environment
Special Test Certificate	Type Test Certificates/Test Report	Confirmation
		Miscellaneous
		Environmental Confirmations
		Environmental Confirmations

Further information


- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8GK9731-0KK20>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/8GK9731-0KK20>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK9731-0KK20

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/6/2021 

