

## Current transformer, class 1, 400/1A, 5VA

**Part no.** ASPIFTUCTC4011  
**Catalog No.** 166312  
**Alternate Catalog No.** ASPIFTUCTC4011



Similar to illustration

## Technical data ETIM 6.0

|                                                                                                                                                           |    |  |                                |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----|--|--------------------------------|
| Low-voltage industrial components (EG000017) / Current transformer (EC002048)                                                                             |    |  |                                |
| Electric engineering, automation, process control engineering / Signal processing / Transformer / Current transformer (ecl@ss8.1-27-21-09-02 [AAB626011]) |    |  |                                |
| Model                                                                                                                                                     |    |  | Through-feed current converter |
| Primary rated current                                                                                                                                     | A  |  | 400                            |
| Secondary rated current                                                                                                                                   | A  |  | 1                              |
| Secondary rated apparent power                                                                                                                            | VA |  | 5                              |
| Accuracy class                                                                                                                                            |    |  | 1                              |
| Over voltage limiting factor                                                                                                                              |    |  | -                              |
| Calibrated                                                                                                                                                |    |  | No                             |
| With shock protection                                                                                                                                     |    |  | No                             |
| Opening height                                                                                                                                            | mm |  | 24                             |
| Opening width                                                                                                                                             | mm |  | 28                             |
| Opening diameter                                                                                                                                          | mm |  | 28                             |
| Snap mounting                                                                                                                                             |    |  | No                             |
| With copper rail                                                                                                                                          |    |  | No                             |
| Secondary connection                                                                                                                                      |    |  | Screw connection               |
| Number of primary inputs                                                                                                                                  |    |  | 0                              |