

Terminal module, 1.5-16mm², 3p, 20mm

Part no. **BBA-TP3/16**
 Catalog No. **107205**



Delivery program

Product range	60 mm system				
Basic function	Connections				
Subrange	Clamp plate				
Material	Silicon free, chlorine free				
Self-extinguishing	to UL 94				
Track resistance	CTI 200				
Temperature resistant	to 120°C				
Connection technique	Spring-loaded terminals				
Width	mm	20			
Pole		3			
Rated operational current	I _e	A	80		
conductor		1.5 - 16 mm ² AWG 16 - AWG 6.  			
Cu factor	kg	0,00			
For use with		12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10			
For use with		Double T profile			
Notes					
○ round conductor, solid					
 Flexible, round conductor with correctly crimped ferrule					
Round conductor, stranded					
 Section conductor, solid					
Sector conductor, stranded					
# CU band					
 CU busbar					

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)

Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])

Busbar thickness	mm	5 - 10
Busbar width	mm	12 - 30
Suitable for		Flat rail
Width clamp	mm	20
Max. conductor cross section	mm ²	16
Max. rated operation current I _e	A	80
Suitable for round conductor connection		Yes
Suitable for sector conductor connection		Yes
Suitable for strip conductor connection		No