

Terminal plate, 3p, copper band up to 32x20 mm, 800A

Part no. **BBA-TP3/CU-BAND**
 Catalog No. **107186**

EL-Nummer
 (Norway) **2465024**



Powering Business Worldwide™

Delivery program

Product range			60 mm system
Basic function			Connections
Subrange			Connection kit
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Track resistance			CTI 200
Temperature resistant			to 120°C
Description			Pole pitch adjustable Fixing direct over busbar terminals Including shroud with adjustable width Looping is possible
Terminal area W x H		mm	32 x 25
Width		mm	180 - 240
Pole			3
Rated operational current	I _e	A	800
conductor			up to # 10 x 32 x 1 mm ■ 30 x 25 mm
Cu factor		kg	0,00
For use with			20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile

Notes

○ round conductor, solid

● Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

💡 Section conductor, solid

Sector conductor, stranded

CU band

■ CU busbar

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)

Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])

Busbar thickness	mm	5 - 10
Busbar width	mm	20 - 30
Suitable for		Flat rail
Width clamp	mm	240
Max. conductor cross section	mm ²	750
Max. rated operation current I _e	A	800
Suitable for round conductor connection		No
Suitable for sector conductor connection		No
Suitable for strip conductor connection		Yes