

**3-component flush-mounting door frame with door, rotary lever, IP54,
HxW=2060x800mm**



Part no.	BPM-U-3S-800/20-P
	111271
EL Number (Norway)	2459723

General specifications

Product name	Eaton xEnergy Basic door frame
Part no.	BPM-U-3S-800/20-P
EAN	4015081108329
Product Length/Depth	70 millimetre
Product height	2065 millimetre
Product width	835 millimetre
Product weight	9.99 kilogram
Compliances	RoHS conform
Product Tradename	xEnergy Basic
Product Type	Accessories
Product Sub Type	Door frame

Delivery program

Type	Additional equipment
Model	Stop door
Application	Moisture-proof (installation site)
Color	Light gray (RAL 7035) Gray

Technical Data - Mechanical

Surface finishing	With powder coating Powder coating
Mounting method	Flush mounting
Material	Aluminum
Degree of protection	IP54 Other
Cover/door type	Rotary lever
Housing material	Aluminum
Suitable for width	800 mm

Additional information

Features	EMC-version
Functions	Additional equipment
Special features	With door

Technical data ETIM 9.0

Cabinet enclosures (EG000011) / Door/operating panel (enclosure/cabinet) (EC000747)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss13-27-18-22-04 [ACN614016])

Model		Stop door
Version as glazed door		No
Version as door for disconnecting switch interlocking		No
Width	mm	835
Height	mm	2065
Depth	mm	70
EMC-version		Yes
Material		Aluminium
Surface finishing		Powder coating
Colour		Grey
Degree of protection (IP)		IP54

