



busbar adapter for SIRIUS breaker for SIRIUS size S3 IEC 100A/690V, UL 100A/600V, AWG4, 25 mm², length 200mm, width 72mm, cable outlet top max. 150° welded on length 153mm, for busbar thickness 5mm und 10 mm, TT-profil

Model	
product brand name	SENTRON
product designation	Device adapter
design of the product	Accessories
Connections	
type of electrical connection	AWG 4
Mechanical Design	
height	200 mm
width of the adapter	72 mm
depth	55 mm
thickness of the busbar	
• minimum	5 mm
busbar center-to-center spacing	60 mm
net weight	650 g
Approvals Certificates	
General Product Approval	



[Confirmation](#)



Test Certificates		Marine / Shipping	
Special Test Certificate	Miscellaneous	Type Test Certificates/Test Report	
			
			
Marine / Shipping		other	Environment
			
		Miscellaneous	Confirmation
			Environmental Confirmations
Environment			
Environmental Con-			

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1211-4TR00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1211-4TR00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1211-4TR00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/31/2022 

