



Fuse-link, 450 A, AC 500 V, 120 kA, NH2, gL/gG, IEC, dual indicator, live gripping lugs

Part no. **NH FUSE 450A 500V GG SIZE 2**  
 Catalog No. **450NHG2B**

EL-Nummer (Norway) **1664076**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	450
Rated voltage			AC 500 V
Construction size			NH2
Utilization category			gL/gG
Status indicator			dual indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2
Optional accessories			fuse-holder SD2-D and SD2-S

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Fuse construction type according to IEC 60269			NH2
Voltage type			AC
Rated current		A	450
Rated voltage AC		V	500
Rated voltage DC		V	
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No
Power loss at rated current		W	31