

## Binary input, flush mounting, 2x230VAC

**Part no.** CBEU-02/03  
**Catalog No.** 182450  
**Alternate Catalog No.** CBEU-02/03  
**EL-Nummer (Norway)** 4560742

## Delivery program

|               |  |               |
|---------------|--|---------------|
| Product Type  |  | Input Output  |
| Mounting type |  | Flush mounted |
| Power supply  |  | Mains         |
| Application   |  | Interface     |

## Technical data ETIM 8.0

|  |    |                         |
|--|----|-------------------------|
| Installation bus systems (EG000032) / Binary input for bus system (EC000688)   |    |                         |
| Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Bus system binary entrance (ecl@ss10.0.1-27-14-31-21 [AKE289014]) |    |                         |
| Bus system KNX   |    | No                      |
| Bus system KNX radio   |    | No                      |
| Bus system radio frequent  |    | Yes                     |
| Bus system LON   |    | No                      |
| Bus system Powernet  |    | No                      |
| Other bus systems  |    | xComfort                |
| Radio frequent bidirectional   |    | Yes                     |
| Mounting method  |    | Flush mounted (plaster) |
| Width in number of modular spacings  |    | 3                       |
| With bus connection  |    | Yes                     |
| Bus module detachable  |    | No                      |
| LED controlling  |    | No                      |
| With LED indication  |    | Yes                     |
| Number of inputs   |    | 2                       |
| Input voltage  | V  | 230 - 230               |
| Type of voltage (input voltage)  |    | AC                      |
| External signal voltage necessary  |    | Yes                     |
| Degree of protection (IP)  |    | IP20                    |
| Min. depth of built-in installation box  | mm | 18                      |