

Contactor, 12 V DC, 3 pole, 380 V 400 V, 4 kW, Contacts N/C = Normally closed= 1 NC, Screw terminals, DC operation



Part no. **DILEM-01-G(12VDC)**
079642

General specifications	
Product name	Eaton Moeller® series DILEM Mini contactor
Part no.	DILEM-01-G(12VDC)
EAN	4015080796428
Product Length/Depth	54 millimetre
Product height	58 millimetre
Product width	45 millimetre
Product weight	0.206 kilogram
Certifications	IEC/EN 60947 VDE 0660 UL File No.: E29096 CSA File No.: 012528 UL UL Category Control No.: NLDX CSA-C22.2 No. 14-05 CE CSA IEC/EN 60947-4-1 UL 508 CSA Class No.: 3211-04
Product Tradename	DILEM
Product Type	Mini contactor
Product Sub Type	None
Catalog Notes	Also tested according to AC-3e.
Features & Functions	
Features	Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module
Fitted with:	Auxiliary contact
General information	
Application	Mini Contactors for Motors and Resistive Loads
Degree of protection	IP20
Lifespan, mechanical	150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A) 200,000 Operations (at 240 V, AC-15) 20,000,000 Operations
Mounting position	As required (except vertical with terminals A1/A2 at the bottom)
Operating frequency	9000 mechanical Operations/h
Overtoltage category	III
Pollution degree	3
Product category	Contactors
Protection	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	6000 V AC
Shock resistance	10 g, N/O main contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/C auxiliary contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 20 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 20 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Suitable for	Also motors with efficiency class IE3
Utilization category	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running AC-4: Normal AC induction motors: starting, plugging, reversing, inching
Voltage type	DC
Climatic environmental conditions	

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Ambient operating temperature (enclosed) - min	25 °C
Ambient operating temperature (enclosed) - max	40 °C
Ambient storage temperature - min	40 °C
Ambient storage temperature - max	80 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacities	
Terminal capacity (flexible with ferrule)	2 x (0.75 - 1.5) mm ² 1 x (0.75 - 1.5) mm ²
Terminal capacity (solid)	1 x (0.75 - 2.5) mm ² 2 x (0.75 - 2.5) mm ²
Terminal capacity (solid/stranded AWG)	18 - 14
Stripping length (main cable)	8 mm
Screw size	M3.5, Terminal screw
Screwdriver size	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
Tightening torque	1.2 Nm, Screw terminals
Electrical rating	
Rated breaking capacity at 220/230 V	90 A
Rated breaking capacity at 380/400 V	90 A
Rated breaking capacity at 500 V	64 A
Rated operational power at AC-3, 240 V, 50 Hz	2.5 kW
Rated operational power at AC-3, 380/400 V, 50 Hz	4 kW
Rated operational power at AC-3, 415 V, 50 Hz	4.3 kW
Rated breaking capacity at 660/690 V	42 A
Rated making capacity up to 440 V (cos phi to IEC/EN 60947)	110 A
Rated operational power at AC-4, 220/230 V, 50 Hz	1.5 kW
Rated operational power at AC-4, 240 V, 50 Hz	1.8 kW
Rated operational power at AC-4, 415 V, 50 Hz	3.1 kW
Rated operational power at AC-4, 440 V, 50 Hz	3.3 kW
Rated operational power at AC-4, 500 V, 50 Hz	3 kW
Rated operational power at AC-4, 660/690 V, 50 Hz	3 kW
Rated operational voltage (Ue) at AC - max	690 V
Rated insulation voltage (Ui)	690 V
Rated operational current (Ie)	2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series) 2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series) 1.5 A at 100 V, DC L/R ≤ 15 ms (with 3 contacts in series)
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V	22 A
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V	6 A
Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V	3 A
Rated operational current (Ie) at AC-15, 500 V	1.5 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V	9 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V	9 A
Rated operational current (Ie) at AC-3, 440 V	9 A
Rated operational current (Ie) at AC-3, 500 V	6.4 A
Rated operational current (Ie) at AC-3, 660 V, 690 V	4.8 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V	6.6 A
Rated operational current (Ie) at AC-4, 440 V	6.6 A
Rated operational current (Ie) at AC-4, 500 V	5 A
Rated operational current (Ie) at AC-4, 660 V, 690 V	3.4 A
Rated operational current (Ie) at DC-1, 110 V	20 A
Rated operational current (Ie) at DC-1, 12 V	20 A
Rated operational current (Ie) at DC-1, 220 V	20 A
Rated operational current (Ie) at DC-1, 24 V	20 A
Rated operational current (Ie) at DC-1, 60 V	20 A

Safe isolation	300 V AC, Between coil and auxiliary contacts, According to EN 61140 300 V AC, Between the contacts, According to EN 61140 300 V AC, Between auxiliary contacts, According to EN 61140 300 V AC, Between coil and contacts, According to EN 61140
Short-circuit rating	
Short-circuit current rating (basic rating)	5 kA, SCCR (UL/CSA) 45 A, max. Fuse, SCCR (UL/CSA)
Short-circuit protection	10 A fast, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding PKZM0-4, Maximum overcurrent protective device, Short-circuit protection only, Auxiliary contacts, Short-circuit rating without welding 6 A gG/gL, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding
Short-circuit protection rating (type 1 coordination) at 500 V	20 A gG/gL
Short-circuit protection rating (type 2 coordination) at 500 V	10 A gG/gL
Conventional thermal current I_{th}	
Conventional thermal current I_{th} (1-pole, enclosed)	40 A
Conventional thermal current I_{th} (3-pole, enclosed)	16 A
Conventional thermal current I_{th} at 55°C (3-pole, open)	19 A
Conventional thermal current I_{th} of auxiliary contacts (1-pole, open)	10 A
Conventional thermal current I_{th} of main contacts (1-pole, open)	50 A
Switching capacity	
Switching capacity (main contacts, general use)	15 A, Maximum motor rating (UL/CSA)
Switching capacity (auxiliary contacts, general use)	10 A, 600 V AC, (UL/CSA) 0.5 A, 250 V DC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
Magnet system	
Arcing time	12 ms at 690 V AC
Changeover time	40 - 50 ms
Duty factor	100 %
Pick-up voltage	0.8 - 1.1 V DC x U_c
Power consumption	Smoothed DC voltage or three-phase bridge rectifier 2.3 VA/W at DC (Pick-up/Sealing power)
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	12 V
Rated control supply voltage (Us) at DC - max	12 V
Switching time (AC operated, N/O, with auxiliary contact module, closing delay)	70 ms
Switching time (DC operated, make contacts, closing delay) - min	26 ms
Switching time (DC operated, make contacts, closing delay) - max	35 ms
Switching time (DC operated, make contacts, opening delay) - min	15 ms
Switching time (DC operated, make contacts, opening delay) - max	25 ms
Motor rating	
Assigned motor power at 115/120 V, 60 Hz, 1-phase	0.5 HP
Assigned motor power at 200/208 V, 60 Hz, 3-phase	2 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase	1.5 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase	3 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase	5 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase	5 HP
Contacts	
Control circuit reliability	< 2 λ , < 1 failure at 100,000,000 Operations (at $U^#$ = 24 V DC, U_{min} = 17 V, I_{min} = 5.4 mA)
Number of auxiliary contacts (normally closed contacts)	1
Number of auxiliary contacts (normally open contacts)	0
Number of contacts (normally closed contacts)	1
Design verification	
Equipment heat dissipation, current-dependent P_{vid}	0.9 W

Heat dissipation capacity P_{diss}	0 W
Heat dissipation per pole, current-dependent P_{vid}	0.3 W
Rated operational current for specified heat dissipation (I_n)	9 A
Static heat dissipation, non-current-dependent P_{vs}	2.3 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])		
Rated control supply voltage U_s at AC 50Hz	V	0 - 0
Rated control supply voltage U_s at AC 60Hz	V	0 - 0
Rated control supply voltage U_s at DC	V	12 - 12
Voltage type for actuating		DC
Rated operation current I_e at AC-1, 400 V	A	22
Rated operation current I_e at AC-3, 400 V	A	9
Rated operation power at AC-3, 400 V	kW	4
Rated operation current I_e at AC-4, 400 V	A	6.6
Rated operation power at AC-4, 400 V	kW	3
Rated operation power NEMA	kW	3.7
Modular version		No
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		1
Type of electrical connection of main circuit		Screw connection
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3