

Replacement coil, Tool-less plug connection, RDC 24: 24 - 27 V DC, DC,
For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45

Part no. DILM32-XSP(RDC24)
Catalog No. 281155
Alternate Catalog XT CERENCOILCTD
No.
EL-Nummer 4130506
(Norway)

Delivery program

Actuating voltage			RDC 24: 24 - 27 V DC
Voltage AC/DC			DC
For use with			DILM17 DILM25 DILM32 DILM38 DILMP32 - DILMP45
For use with			DILM17 - DILM38

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	0 - 0
Rated control supply voltage Us at AC 60HZ		V	0 - 0
Rated control supply voltage Us at DC		V	24 - 27
Voltage type for actuating			DC