

Replacement coil, Tool-less plug connection, RAC 120: 100 - 120 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200



Powering Business Worldwide™

**Part no.** DILM150-XSP(RAC120)  
**Catalog No.** 230111  
**Alternate Catalog No.** XTCERENCOILGA

### Delivery program

|                   |  |  |  |
|-------------------|--|--|--|
| Actuating voltage |  |  | RAC 120: 100 - 120 V 50/60 Hz                        |
| Voltage AC/DC     |  |  | AC   |
| For use with      |  |  | DILM115<br>DILM150<br>DILM170<br>DILMP125 - DILMP200 |
| For use with      |  |  | DILM115 - DILM170 (incl. electronic module)          |

### Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 60  |

### Technical data ETIM 8.0

|  |  |   |           |
|--|--|---|-----------|
| Low-voltage industrial components (EG000017) / Coil for relay (EC001043)   |  |   |           |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013]) |  |   |           |
| Rated control supply voltage Us at AC 50HZ   |  | V | 100 - 120 |
| Rated control supply voltage Us at AC 60HZ   |  | V | 100 - 120 |
| Rated control supply voltage Us at DC  |  | V | 0 - 0     |
| Voltage type for actuating   |  |   | AC        |