

Replacement coil, 220 V 50 Hz, 240 V 60 Hz, AC operation, For use with:
DILM250-S, DILM300A-S



Part no. DILM250-S-XSP/E(220-240V50/60HZ)
Catalog No. 274202
Alternate Catalog No. XTCSRENCOILLB

Delivery program

Actuating voltage			220 V 50 Hz, 240 V 60 Hz
Voltage AC/DC			AC operation
For use with			DILM185-S DILM225-S DILM250-S DILM300A-S
Instructions			The following items are predecessor models and are no longer available: DILM185(-S), DILM225(-S), DILM300(-S)

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	60

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	220 - 240
Rated control supply voltage Us at AC 60HZ		V	220 - 240
Rated control supply voltage Us at DC		V	0 - 0
Voltage type for actuating			AC