

Replacement coil, Tool-less plug connection, RAC 240: 190 - 240 V 50/60 Hz, AC, For use with: DILM185A, DILM225A



**Part no.** DILM225A-XSP(RAC240)  
**Catalog No.** 139565  
**Alternate Catalog No.** XTCERENCOILHB

### Delivery program

|                   |  |  |   |
|-------------------|--|--|---|
| Actuating voltage |  |  | RAC 240: 190 - 240 V 50/60 Hz                 |
| Voltage AC/DC     |  |  | AC  |
| For use with      |  |  | DILM185A<br>DILM225A                          |
| For use with      |  |  | DILM185A - DILM225A (incl. electronic module) |

### Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -40 |
| Operating ambient temperature max.     |  | °C | 60  |

### Technical data ETIM 8.0

|  |  |   |           |
|--|--|---|-----------|
| Low-voltage industrial components (EG000017) / Coil for relay (EC001043)   |  |   |           |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013]) |  |   |           |
| Rated control supply voltage Us at AC 50HZ   |  | V | 190 - 240 |
| Rated control supply voltage Us at AC 60HZ   |  | V | 190 - 240 |
| Rated control supply voltage Us at DC  |  | V | 0 - 0     |
| Voltage type for actuating   |  |   | AC        |