

Replacement coil, Tool-less plug connection, 110 V 50 Hz, 120 V 60 Hz, AC,  
For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45



Powering Business Worldwide™

**Part no.** DILM32-XSP(110V50HZ,120V60HZ)  
**Catalog No.** 281138  
**Alternate Catalog No.** XTCERENCOILCA

### Delivery program

Actuating voltage			110 V 50 Hz, 120 V 60 Hz
Voltage AC/DC			AC
For use with			DILM17 DILM25 DILM32 DILM38 DILMP32 - DILMP45
For use with			DILM17 - DILM38

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60

### Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	110 - 120
Rated control supply voltage Us at AC 60HZ		V	120 - 120
Rated control supply voltage Us at DC		V	0 - 0
Voltage type for actuating			AC