

**Contactor, 3 pole, 380 V 400 V 18.5 kW, 1 NC, 24 V 50/60 Hz, AC operation,  
Screw terminals**

**Part no.** DILM38-01(24V50/60HZ)  
**Catalog No.** 112460  
**Alternate Catalog No.** XTCE038C01T

## Delivery program

|                      |  |  |                                                                                                                                                                                                                            |
|----------------------|--|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product range        |  |  | Contactors                                                                                                                                                                                                                 |
| Application          |  |  | Contactors for Motors                                                                                                                                                                                                      |
| Subrange             |  |  | Contactors up to 170 A, 3 pole                                                                                                                                                                                             |
| Utilization category |  |  | AC-1: Non-inductive or slightly inductive loads, resistance furnaces<br>NAC-3: Normal AC induction motors: starting, switch off during running<br>AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| Notes                |  |  | Not suitable for motors with efficiency class IE3.                                                                                                                                                                         |
| Connection technique |  |  | Screw terminals                                                                                                                                                                                                            |
| Number of poles      |  |  | 3 pole                                                                                                                                                                                                                     |

### Rated operational current

|                                                           |                                  |   |                                                    |
|-----------------------------------------------------------|----------------------------------|---|----------------------------------------------------|
| AC-3                                                      |                                  |   |                                                    |
| Notes                                                     |                                  |   | At maximum permissible ambient temperature (open.) |
| 380 V 400 V                                               | I <sub>e</sub>                   | A | 38                                                 |
| AC-1                                                      |                                  |   |                                                    |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                                  |   |                                                    |
| Open                                                      |                                  |   |                                                    |
| at 40 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A | 45                                                 |
| enclosed                                                  | I <sub>th</sub>                  | A | 36                                                 |
| Conventional free air thermal current, 1 pole             |                                  |   |                                                    |
| open                                                      | I <sub>th</sub>                  | A | 100                                                |
| enclosed                                                  | I <sub>th</sub>                  | A | 90                                                 |

### Max. rating for three-phase motors, 50 - 60 Hz

|             |   |    |      |
|-------------|---|----|------|
| AC-3        |   |    |      |
| 220 V 230 V | P | kW | 11   |
| 380 V 400 V | P | kW | 18.5 |
| 660 V 690 V | P | kW | 21   |
| AC-4        |   |    |      |
| 220 V 230 V | P | kW | 4    |
| 380 V 400 V | P | kW | 7    |
| 660 V 690 V | P | kW | 10   |

### Contacts

|                                        |  |  |                                                           |
|----------------------------------------|--|--|-----------------------------------------------------------|
| N/C = Normally closed                  |  |  | 1 NC                                                      |
| Can be combined with auxiliary contact |  |  | DILA-XHI(V)...(-PI)<br>DILM32-XHI...-PI<br>DILM32-XHI11-S |
| Actuating voltage                      |  |  | 24 V 50/60 Hz                                             |
| Voltage AC/DC                          |  |  | AC operation                                              |
| Connection to SmartWire-DT             |  |  | no                                                        |
| <b>Instructions</b>                    |  |  | Contacts to EN 50 012.<br>with mirror contact.            |
| Frame size                             |  |  | 2                                                         |

## Technical data

|                      |            |                   |                                 |
|----------------------|------------|-------------------|---------------------------------|
| Standards            |            |                   | IEC/EN 60947, VDE 0660, UL, CSA |
| Lifespan, mechanical |            |                   |                                 |
| AC operated          | Operations | x 10 <sup>6</sup> | 10                              |

|                                                                       |                  |      |                                                                                |
|-----------------------------------------------------------------------|------------------|------|--------------------------------------------------------------------------------|
| Operating frequency, mechanical                                       |                  |      |                                                                                |
| AC operated                                                           | Operations/h     |      | 5000                                                                           |
| Climatic proofing                                                     |                  |      | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature                                                   |                  |      |                                                                                |
| Open                                                                  | °C               |      | -25 - +60                                                                      |
| Enclosed                                                              | °C               |      | - 25 - 40                                                                      |
| Storage                                                               | °C               |      | - 40 - 80                                                                      |
| Mechanical shock resistance (IEC/EN 60068-2-27)                       |                  |      |                                                                                |
| Half-sinusoidal shock, 10 ms                                          |                  |      |                                                                                |
| Main contacts                                                         |                  |      |                                                                                |
| N/O contact                                                           | g                |      | 10                                                                             |
| Auxiliary contacts                                                    |                  |      |                                                                                |
| N/O contact                                                           | g                |      | 7                                                                              |
| N/C contact                                                           | g                |      | 5                                                                              |
| Mechanical shock resistance (IEC/EN 60068-2-27) when tabletop-mounted |                  |      |                                                                                |
| Half-sinusoidal shock, 10 ms                                          |                  |      |                                                                                |
| Main contacts                                                         |                  |      |                                                                                |
| N/O contact                                                           | g                |      | 6.9                                                                            |
| Auxiliary contacts                                                    |                  |      |                                                                                |
| N/O contact                                                           | g                |      | 5.3                                                                            |
| N/C contact                                                           | g                |      | 3.5                                                                            |
| Degree of Protection                                                  |                  |      | IP00                                                                           |
| Protection against direct contact when actuated from front (EN 50274) |                  |      | Finger and back-of-hand proof                                                  |
| Altitude                                                              | m                |      | Max. 2000                                                                      |
| Weight                                                                |                  |      |                                                                                |
| AC operated                                                           | kg               |      | 0.428                                                                          |
| Screw connector terminals                                             |                  |      |                                                                                |
| Terminal capacity main cable                                          |                  |      |                                                                                |
| Solid                                                                 | mm <sup>2</sup>  |      | 1 x (0.75 - 16)<br>2 x (0.75 - 10)                                             |
| Flexible with ferrule                                                 | mm <sup>2</sup>  |      | 1 x (0.75 - 16)<br>2 x (0.75 - 10)                                             |
| Stranded                                                              | mm <sup>2</sup>  |      | 1 x 16                                                                         |
| Solid or stranded                                                     | AWG              |      | single 18 - 6, double 18 - 8                                                   |
| Stripping length                                                      | mm               |      | 10                                                                             |
| Terminal screw                                                        |                  |      | M5                                                                             |
| Tightening torque                                                     | Nm               |      | 3.2                                                                            |
| Tool                                                                  |                  |      |                                                                                |
| Pozidriv screwdriver                                                  | Size             |      | 2                                                                              |
| Standard screwdriver                                                  | mm               |      | 0.8 x 5.5<br>1 x 6                                                             |
| Terminal capacity control circuit cables                              |                  |      |                                                                                |
| Solid                                                                 | mm <sup>2</sup>  |      | 1 x (0.75 - 4)<br>2 x (0.75 - 2.5)                                             |
| Flexible with ferrule                                                 | mm <sup>2</sup>  |      | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5)                                           |
| Solid or stranded                                                     | AWG              |      | 18 - 14                                                                        |
| Stripping length                                                      | mm               |      | 10                                                                             |
| Terminal screw                                                        |                  |      | M3.5                                                                           |
| Tightening torque                                                     | Nm               |      | 1.2                                                                            |
| Tool                                                                  |                  |      |                                                                                |
| Pozidriv screwdriver                                                  | Size             |      | 2                                                                              |
| Standard screwdriver                                                  | mm               |      | 0.8 x 5.5<br>1 x 6                                                             |
| <b>Main conducting paths</b>                                          |                  |      |                                                                                |
| Rated impulse withstand voltage                                       | U <sub>imp</sub> | V AC | 8000                                                                           |
| Overvoltage category/pollution degree                                 |                  |      | III/3                                                                          |

|                                        |                |      |     |
|----------------------------------------|----------------|------|-----|
| Rated insulation voltage               | U <sub>i</sub> | V AC | 690 |
| Rated operational voltage              | U <sub>e</sub> | V AC | 690 |
| Safe isolation to EN 61140             |                |      |     |
| between coil and contacts              |                | V AC | 440 |
| between the contacts                   |                | V AC | 440 |
| Making capacity (p.f. to IEC/EN 60947) |                |      |     |
|                                        | Up to 690 V    | A    | 384 |
| Breaking capacity                      |                |      |     |
| 220 V 230 V                            |                | A    | 320 |
| 380 V 400 V                            |                | A    | 320 |
| 500 V                                  |                | A    | 320 |
| 660 V 690 V                            |                | A    | 180 |
| Short-circuit rating                   |                |      |     |
| Short-circuit protection maximum fuse  |                |      |     |
| Type "2" coordination                  |                |      |     |
| 400 V                                  | gG/gL 500 V    | A    | 63  |
| 690 V                                  | gG/gL 690 V    | A    | 35  |
| Type "1" coordination                  |                |      |     |
| 400 V                                  | gG/gL 500 V    | A    | 125 |
| 690 V                                  | gG/gL 690 V    | A    | 63  |

## AC

|                                                           |                                  |     |                                                    |
|-----------------------------------------------------------|----------------------------------|-----|----------------------------------------------------|
| AC-1                                                      |                                  |     |                                                    |
| Rated operational current                                 |                                  |     |                                                    |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                                  |     |                                                    |
| Open                                                      |                                  |     |                                                    |
| at 40 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A   | 45                                                 |
| at 50 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A   | 43                                                 |
| at 55 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A   | 42                                                 |
| at 60 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A   | 40                                                 |
| enclosed                                                  | I <sub>th</sub>                  | A   | 36                                                 |
| Conventional free air thermal current, 1 pole             |                                  |     |                                                    |
| open                                                      | I <sub>th</sub>                  | A   | 100                                                |
| enclosed                                                  | I <sub>th</sub>                  | A   | 90                                                 |
| AC-3                                                      |                                  |     |                                                    |
| Rated operational current                                 |                                  |     |                                                    |
| Open, 3-pole: 50 – 60 Hz                                  |                                  |     |                                                    |
| Notes                                                     |                                  |     | At maximum permissible ambient temperature (open.) |
| 220 V 230 V                                               | I <sub>e</sub>                   | A   | 38                                                 |
| 240 V                                                     | I <sub>e</sub>                   | A   | 38                                                 |
| 380 V 400 V                                               | I <sub>e</sub>                   | A   | 38                                                 |
| 415 V                                                     | I <sub>e</sub>                   | A   | 38                                                 |
| 440V                                                      | I <sub>e</sub>                   | A   | 38                                                 |
| 500 V                                                     | I <sub>e</sub>                   | A   | 38                                                 |
| 660 V 690 V                                               | I <sub>e</sub>                   | A   | 22.5                                               |
| Motor rating                                              | P                                | kWh |                                                    |
| 220 V 230 V                                               | P                                | kW  | 11                                                 |
| 240V                                                      | P                                | kW  | 12                                                 |
| 380 V 400 V                                               | P                                | kW  | 18.5                                               |
| 415 V                                                     | P                                | kW  | 20                                                 |
| 440 V                                                     | P                                | kW  | 21                                                 |
| 500 V                                                     | P                                | kW  | 24                                                 |
| 660 V 690 V                                               | P                                | kW  | 21                                                 |
| AC-4                                                      |                                  |     |                                                    |
| Open, 3-pole: 50 – 60 Hz                                  |                                  |     |                                                    |

|              |                |     |     |
|--------------|----------------|-----|-----|
| 220 V 230 V  | I <sub>e</sub> | A   | 15  |
| 240 V        | I <sub>e</sub> | A   | 15  |
| 380 V 400 V  | I <sub>e</sub> | A   | 15  |
| 415 V        | I <sub>e</sub> | A   | 15  |
| 440 V        | I <sub>e</sub> | A   | 15  |
| 500 V        | I <sub>e</sub> | A   | 15  |
| 660 V 690 V  | I <sub>e</sub> | A   | 12  |
| Motor rating | P              | kWh |     |
| 220 V 230 V  | P              | kW  | 4   |
| 240 V        | P              | kW  | 4.5 |
| 380 V 400 V  | P              | kW  | 7   |
| 415 V        | P              | kW  | 7.5 |
| 440 V        | P              | kW  | 8   |
| 500 V        | P              | kW  | 9   |
| 660 V 690 V  | P              | kW  | 10  |

DC

|                                 |                |   |    |
|---------------------------------|----------------|---|----|
| Rated operational current, open |                |   |    |
| DC-1                            |                |   |    |
| 60 V                            | I <sub>e</sub> | A | 40 |
| 110 V                           | I <sub>e</sub> | A | 40 |
| 220 V                           | I <sub>e</sub> | A | 40 |

Current heat loss

|                                                   |  |    |      |
|---------------------------------------------------|--|----|------|
| 3 pole, at I <sub>th</sub> (60°)                  |  | W  | 10.3 |
| Current heat loss at I <sub>e</sub> to AC-3/400 V |  | W  | 9.3  |
| Impedance per pole                                |  | mΩ | 2.7  |

Magnet systems

|                                                                        |          |                   |                                                                                    |
|------------------------------------------------------------------------|----------|-------------------|------------------------------------------------------------------------------------|
| Voltage tolerance                                                      |          |                   |                                                                                    |
| AC operated                                                            | Pick-up  | x U <sub>c</sub>  | 0.8 - 1.1                                                                          |
| Drop-out voltage AC operated                                           | Drop-out | x U <sub>c</sub>  | 0.3 - 0.6                                                                          |
| Power consumption of the coil in a cold state and 1.0 x U <sub>S</sub> |          |                   |                                                                                    |
| 50/60 Hz                                                               | Pick-up  | VA                | 62<br>58                                                                           |
| 50/60 Hz                                                               | Sealing  | VA                | 9.1<br>6.5                                                                         |
| 50/60 Hz                                                               | Sealing  | W                 | 2.1                                                                                |
| Duty factor                                                            |          | % DF              | 100                                                                                |
| Changeover time at 100 % U <sub>S</sub> (recommended value)            |          |                   |                                                                                    |
| Main contacts                                                          |          |                   |                                                                                    |
| AC operated                                                            |          |                   |                                                                                    |
| Closing delay                                                          |          | ms                | 16 - 22                                                                            |
| Opening delay                                                          |          | ms                | 8 - 14                                                                             |
| Arcing time                                                            |          | ms                | 10                                                                                 |
| Lifespan, mechanical; Coil 50/60 Hz                                    |          | x 10 <sup>6</sup> | Mechanical lifespan at 50 Hz approx. 30% lower than under → Technical data general |

Electromagnetic compatibility (EMC)

|                       |  |  |               |
|-----------------------|--|--|---------------|
| Emitted interference  |  |  | to EN 60947-1 |
| Interference immunity |  |  | to EN 60947-1 |

Rating data for approved types

|                      |  |    |    |
|----------------------|--|----|----|
| Switching capacity   |  |    |    |
| Maximum motor rating |  |    |    |
| Three-phase          |  |    |    |
| 200 V<br>208 V       |  | HP | 10 |
| 230 V<br>240 V       |  | HP | 10 |
| 460 V<br>480 V       |  | HP | 20 |
| 575 V                |  | HP | 25 |

|                                                           |      |                 |  |
|-----------------------------------------------------------|------|-----------------|--|
| 600 V                                                     |      |                 |  |
| Single-phase                                              |      |                 |  |
| 115 V<br>120 V                                            | HP   | 2               |  |
| 230 V<br>240 V                                            | HP   | 5               |  |
| General use                                               | A    | 40              |  |
| Auxiliary contacts                                        |      |                 |  |
| Pilot Duty                                                |      |                 |  |
| AC operated                                               |      | A600            |  |
| DC operated                                               |      | P300            |  |
| General Use                                               |      |                 |  |
| AC                                                        | V    | 600             |  |
| AC                                                        | A    | 10              |  |
| DC                                                        | V    | 250             |  |
| DC                                                        | A    | 1               |  |
| Short Circuit Current Rating                              | SCCR |                 |  |
| Basic Rating                                              |      |                 |  |
| SCCR                                                      | kA   | 5               |  |
| max. Fuse                                                 | A    | 125             |  |
| max. CB                                                   | A    | 125             |  |
| 480 V High Fault                                          |      |                 |  |
| SCCR (fuse)                                               | kA   | 10/100          |  |
| max. Fuse                                                 | A    | 125/70 Class J  |  |
| SCCR (CB)                                                 | kA   | 10/65           |  |
| max. CB                                                   | A    | 50/32           |  |
| 600 V High Fault                                          |      |                 |  |
| SCCR (fuse)                                               | kA   | 10/100          |  |
| max. Fuse                                                 | A    | 125/125 Class J |  |
| SCCR (CB)                                                 | kA   | 10/22           |  |
| max. CB                                                   | A    | 50/32           |  |
| Special Purpose Ratings                                   |      |                 |  |
| Electrical Discharge Lamps (Ballast)                      |      |                 |  |
| 480V 60Hz 3phase, 277V 60Hz 1phase                        | A    | 40              |  |
| 600V 60Hz 3phase, 347V 60Hz 1phase                        | A    | 40              |  |
| Incandescent Lamps (Tungsten)                             |      |                 |  |
| 480V 60Hz 3phase, 277V 60Hz 1phase                        | A    | 40              |  |
| 600V 60Hz 3phase, 347V 60Hz 1phase                        | A    | 40              |  |
| Resistance Air Heating                                    |      |                 |  |
| 480V 60Hz 3phase, 277V 60Hz 1phase                        | A    | 40              |  |
| 600V 60Hz 3phase, 347V 60Hz 1phase                        | A    | 40              |  |
| Refrigeration Control (CSA only)                          |      |                 |  |
| LRA 480V 60Hz 3phase                                      | A    | 240             |  |
| FLA 480V 60Hz 3phase                                      | A    | 40              |  |
| LRA 600V 60Hz 3phase                                      | A    | 180             |  |
| FLA 600V 60Hz 3phase                                      | A    | 30              |  |
| Definite Purpose Ratings (100,000 cycles acc. to UL 1995) |      |                 |  |
| LRA 480V 60Hz 3phase                                      | A    | 192             |  |
| FLA 480V 60Hz 3phase                                      | A    | 32              |  |
| Elevator Control                                          |      |                 |  |
| 200V 60Hz 3phase                                          | HP   | 7.5             |  |
| 200V 60Hz 3phase                                          | A    | 25.3            |  |
| 240V 60Hz 3phase                                          | HP   | 7.5             |  |
| 240V 60Hz 3phase                                          | A    | 22              |  |
| 480V 60Hz 3phase                                          | HP   | 20              |  |
| 480V 60Hz 3phase                                          | A    | 27              |  |

|                  |    |    |
|------------------|----|----|
| 600V 60Hz 3phase | HP | 20 |
| 600V 60Hz 3phase | A  | 22 |

### Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                                                                                                                  |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 38                                                                                                                               |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 3.1                                                                                                                              |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 9.3                                                                                                                              |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 2.1                                                                                                                              |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                                                |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                                                                                                              |
| Operating ambient temperature max.                                                                                     |                   | °C | 60                                                                                                                               |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                                                  |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                                                  |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                                                                                 |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                                                                                             |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                                                                                    |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                                                                              |                   |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

### Technical data ETIM 8.0

|                                                                                                                                                                                       |    |  |         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|--|---------|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)                                                                                               |    |  |         |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015]) |    |  |         |
| Rated control supply voltage Us at AC 50HZ                                                                                                                                            | V  |  | 24 - 24 |
| Rated control supply voltage Us at AC 60HZ                                                                                                                                            | V  |  | 24 - 24 |
| Rated control supply voltage Us at DC                                                                                                                                                 | V  |  | 0 - 0   |
| Voltage type for actuating                                                                                                                                                            |    |  | AC      |
| Rated operation current Ie at AC-1, 400 V                                                                                                                                             | A  |  | 45      |
| Rated operation current Ie at AC-3, 400 V                                                                                                                                             | A  |  | 38      |
| Rated operation power at AC-3, 400 V                                                                                                                                                  | kW |  | 18.5    |
| Rated operation current Ie at AC-4, 400 V                                                                                                                                             | A  |  | 15      |
| Rated operation power at AC-4, 400 V                                                                                                                                                  | kW |  | 7       |
| Rated operation power NEMA                                                                                                                                                            | kW |  | 14.9    |
| Modular version                                                                                                                                                                       |    |  | No      |
| Number of auxiliary contacts as normally open contact                                                                                                                                 |    |  | 0       |

|                                                         |  |  |                  |
|---------------------------------------------------------|--|--|------------------|
| Number of auxiliary contacts as normally closed contact |  |  | 1                |
| Type of electrical connection of main circuit           |  |  | Screw connection |
| Number of normally closed contacts as main contact      |  |  | 0                |
| Number of normally open contacts as main contact        |  |  | 3                |