

**Contactor, 4 pole, AC operation: 160 A, RAC 120: 100 - 120 V 50/60 Hz,  
Screw terminals**

**Part no.** DILMP160(RAC120)  
**Catalog No.** 109913  
**Alternate Catalog No.** XTCTF160G00A  
**EL-Nummer (Norway)** 4110200

## Delivery program

|                                                           |                |   |                                                                                                                                                       |
|-----------------------------------------------------------|----------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product range                                             |                |   | Contactors                                                                                                                                            |
| Application                                               |                |   | Contactors for 4 pole electric consumers                                                                                                              |
| Subrange                                                  |                |   | Contactors up to 200 A, 4 pole                                                                                                                        |
| Utilization category                                      |                |   | AC-1: Non-inductive or slightly inductive loads, resistance furnaces<br>AC-3/AC-3e: Normal AC induction motors: Starting, switching off while running |
| Connection technique                                      |                |   | Screw terminals                                                                                                                                       |
| Number of poles                                           |                |   | 4 pole                                                                                                                                                |
| <b>Rated operational current</b>                          |                |   |                                                                                                                                                       |
| AC-1                                                      |                |   |                                                                                                                                                       |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                |   |                                                                                                                                                       |
| at 40 °C                                                  | $I_{th} = I_e$ | A | 160                                                                                                                                                   |
| at 50 °C                                                  | $I_{th} = I_e$ | A | 150                                                                                                                                                   |
| at 55 °C                                                  | $I_{th} = I_e$ | A | 143                                                                                                                                                   |
| at 60 °C                                                  | $I_{th} = I_e$ | A | 138                                                                                                                                                   |
| For use with                                              |                |   | DILM150-XHI(A)(V)...<br>DILM1000-XHI(V)...                                                                                                            |
| Actuating voltage                                         |                |   | RAC 120: 100 - 120 V 50/60 Hz                                                                                                                         |
| Voltage AC/DC                                             |                |   | AC operation                                                                                                                                          |
| Connection to SmartWire-DT                                |                |   | no                                                                                                                                                    |
| <b>Instructions</b>                                       |                |   | Contacts to EN 50 012.<br>integrated suppressor circuit in actuating electronics                                                                      |

## Technical data

### General

|                                                                       |              |               |                                                                               |
|-----------------------------------------------------------------------|--------------|---------------|-------------------------------------------------------------------------------|
| Standards                                                             |              |               | IEC/EN 60947, VDE 0660, UL, CSA                                               |
| Lifespan, mechanical                                                  |              |               |                                                                               |
| AC operated                                                           | Operations   | $\times 10^6$ | 5.7                                                                           |
| Operating frequency, mechanical                                       |              |               |                                                                               |
| AC operated                                                           | Operations/h |               | 3600                                                                          |
| DC operated                                                           | Operations/h |               | 3600                                                                          |
| Climatic proofing                                                     |              |               | Damp heat, constant, to IEC 60068-2-3<br>Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature                                                   |              |               |                                                                               |
| Open                                                                  |              | °C            | -25 - +60                                                                     |
| Enclosed                                                              |              | °C            | - 25 - 40                                                                     |
| Storage                                                               |              | °C            | - 40 - 80                                                                     |
| Mechanical shock resistance (IEC/EN 60068-2-27)                       |              |               |                                                                               |
| Half-sinusoidal shock, 10 ms                                          |              |               |                                                                               |
| Main contacts                                                         |              |               |                                                                               |
| N/O contact                                                           |              | g             | 10                                                                            |
| Auxiliary contacts                                                    |              |               |                                                                               |
| N/O contact                                                           |              | g             | 7                                                                             |
| N/C contact                                                           |              | g             | 5                                                                             |
| Degree of Protection                                                  |              |               | IP00                                                                          |
| Altitude                                                              |              | m             | Max. 2000                                                                     |
| Protection against direct contact when actuated from front (EN 50274) |              |               | Finger and back-of-hand proof                                                 |

|                                          |                                     |                 |                                      |
|------------------------------------------|-------------------------------------|-----------------|--------------------------------------|
| Stripping length                         |                                     | mm              | 15                                   |
| Terminal capacity main cable             |                                     |                 |                                      |
| Flexible with ferrule                    |                                     | mm <sup>2</sup> | 1 x (10 - 95)<br>2 x (10 - 70)       |
| Stranded                                 |                                     | mm <sup>2</sup> | 1 x (16 - 120)<br>2 x (16 - 95)      |
| Solid or stranded                        |                                     | AWG             | 8 - 3/0                              |
| Flat conductor                           | Lamellenzahl<br>x Breite x<br>Dicke | mm              | 2 x (6 x 16 x 0.8)                   |
| Terminal screw                           |                                     |                 | M10                                  |
| Tightening torque                        |                                     | Nm              | 14                                   |
| Stripping length                         |                                     | mm              | 15                                   |
| Terminal capacity control circuit cables |                                     |                 |                                      |
| Solid                                    |                                     | mm <sup>2</sup> | 1 x (0.75 - 4)<br>2 x (0.75 - 4)     |
| Flexible with ferrule                    |                                     | mm <sup>2</sup> | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5) |
| Solid or stranded                        |                                     | AWG             | 18 - 14                              |
| Stripping length                         |                                     | mm              | 10                                   |
| Terminal screw                           |                                     |                 | M3.5                                 |
| Tightening torque                        |                                     | Nm              | 1.2                                  |
| Tool                                     |                                     |                 |                                      |
| Main cable                               |                                     |                 |                                      |
| Hexagon socket-head spanner              | SW                                  | mm              | 5                                    |
| Control circuit cables                   |                                     |                 |                                      |
| Pozidriv screwdriver                     |                                     | Size            | 2                                    |
| Standard screwdriver                     |                                     | mm              | 0.8 x 5.5<br>1 x 6                   |

Main conducting paths

|                                       |                  |      |                                   |
|---------------------------------------|------------------|------|-----------------------------------|
| Rated impulse withstand voltage       | U <sub>imp</sub> | V AC | 8000                              |
| Overvoltage category/pollution degree |                  |      | III/3                             |
| Rated insulation voltage              | U <sub>i</sub>   | V AC | 690                               |
| Rated operational voltage             | U <sub>e</sub>   | V AC | 690                               |
| Safe isolation to EN 61140            |                  |      |                                   |
| between coil and contacts             |                  | V AC | 440                               |
| between the contacts                  |                  | V AC | 440                               |
| Making capacity (cos φ)               | Up to 690 V      | A    | 1330<br>According to IEC/EN 60947 |
| Breaking capacity                     |                  |      |                                   |
| 220 V 230 V                           |                  | A    | 950                               |
| 380 V 400 V                           |                  | A    | 950                               |
| 500 V                                 |                  | A    | 950                               |
| 660 V 690 V                           |                  | A    | 750                               |
| Short-circuit rating                  |                  |      |                                   |
| Short-circuit protection maximum fuse |                  |      |                                   |
| Type “2” coordination                 |                  |      |                                   |
| 400 V                                 | gG/gL 500 V      | A    | 160                               |
| 690 V                                 | gG/gL 690 V      | A    | 160                               |
| Type “1” coordination                 |                  |      |                                   |
| 400 V                                 | gG/gL 500 V      | A    | 250                               |
| 690 V                                 | gG/gL 690 V      | A    | 200                               |

AC

|                                                           |                                  |   |     |
|-----------------------------------------------------------|----------------------------------|---|-----|
| AC-1                                                      |                                  |   |     |
| Rated operational current                                 |                                  |   |     |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                                  |   |     |
| Open                                                      |                                  |   |     |
| at 40 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A | 160 |
| at 50 °C                                                  | I <sub>th</sub> = I <sub>e</sub> | A | 150 |

|                                               |                |     |                                                                                       |
|-----------------------------------------------|----------------|-----|---------------------------------------------------------------------------------------|
| at 55 °C                                      | $I_{th} = I_e$ | A   | 143                                                                                   |
| at 60 °C                                      | $I_{th} = I_e$ | A   | 138                                                                                   |
| enclosed                                      | $I_{th}$       | A   | 128                                                                                   |
| Conventional free air thermal current, 1 pole |                |     |                                                                                       |
| open                                          | $I_{th}$       | A   | 415                                                                                   |
| enclosed                                      | $I_{th}$       | A   | 373                                                                                   |
| Motor rating                                  | P              | kWh |                                                                                       |
| 220/230 V                                     | P              | kW  | 58                                                                                    |
| 240 V                                         | P              | kW  | 63                                                                                    |
| 380/400 V                                     | P              | kW  | 100                                                                                   |
| 415 V                                         | P              | kW  | 109                                                                                   |
| 440 V                                         | P              | kW  | 116                                                                                   |
| 500 V                                         | P              | kW  | 132                                                                                   |
| 690 V                                         | P              | kW  | 174                                                                                   |
| AC-3                                          |                |     |                                                                                       |
| Rated operational current                     |                |     |                                                                                       |
| Open, 3-pole: 50 – 60 Hz                      |                |     |                                                                                       |
| Notes                                         |                |     | At maximum permissible ambient temperature (open.)<br>Also tested according to AC-3e. |
| 220 V 230 V                                   | $I_e$          | A   | 95                                                                                    |
| 240 V                                         | $I_e$          | A   | 95                                                                                    |
| 380 V 400 V                                   | $I_e$          | A   | 95                                                                                    |
| 415 V                                         | $I_e$          | A   | 95                                                                                    |
| 440V                                          | $I_e$          | A   | 95                                                                                    |
| 500 V                                         | $I_e$          | A   | 95                                                                                    |
| 660 V 690 V                                   | $I_e$          | A   | 80                                                                                    |
| Motor rating                                  | P              | kWh |                                                                                       |
| 220 V 230 V                                   | P              | kW  | 30                                                                                    |
| 240V                                          | P              | kW  | 33                                                                                    |
| 380 V 400 V                                   | P              | kW  | 45                                                                                    |
| 415 V                                         | P              | kW  | 57                                                                                    |
| 440 V                                         | P              | kW  | 60                                                                                    |
| 500 V                                         | P              | kW  | 70                                                                                    |
| 660 V 690 V                                   | P              | kW  | 75                                                                                    |

## DC

|                                 |       |   |     |
|---------------------------------|-------|---|-----|
| Rated operational current, open |       |   |     |
| DC-1                            |       |   |     |
| 60 V                            | $I_e$ | A | 160 |
| 110 V                           | $I_e$ | A | 160 |
| 220 V                           | $I_e$ | A | 160 |

## Current heat loss

|                           |    |      |
|---------------------------|----|------|
| 3 pole, at $I_{th}$ (60°) | W  | 36.3 |
| Impedance per pole        | mΩ | 0.6  |

## Magnet systems

|                                                               |          |         |            |
|---------------------------------------------------------------|----------|---------|------------|
| Voltage tolerance                                             |          |         |            |
| AC operated 50 Hz                                             | Pick-up  | x $U_c$ | 0.8 - 1.15 |
| AC operated 50/60 Hz                                          |          | x $U_c$ | 0.8 - 1.15 |
| Drop-out voltage AC operated                                  | Drop-out | x $U_c$ | 0.25 - 0.6 |
| Power consumption of the coil in a cold state and 1.0 x $U_S$ |          |         |            |
| AC operated 50/60 Hz                                          | Pick-up  | VA      | 180        |
| AC operated 50/60 Hz                                          | Pick-up  | W       | 150        |
| AC operated 50/60 Hz                                          | Sealing  | VA      | 3.1        |
| AC operated 50/60 Hz                                          | Sealing  | W       | 2.3        |
| Duty factor                                                   |          | % DF    | 100        |
| Changeover time at 100 % $U_S$ (recommended value)            |          |         |            |

|                                                                                            |  |    |         |
|--------------------------------------------------------------------------------------------|--|----|---------|
| Main contacts                                                                              |  |    |         |
| AC operated                                                                                |  |    |         |
| Closing delay                                                                              |  | ms | 28 - 33 |
| Opening delay                                                                              |  | ms | 35 - 41 |
| Permissible residual current with actuation of A1 - A2 by the electronics (with 0 signal). |  | mA | ≤ 1     |

#### Rating data for approved types

|                                      |  |      |                 |
|--------------------------------------|--|------|-----------------|
| Switching capacity                   |  |      |                 |
| Maximum motor rating                 |  |      |                 |
| Three-phase                          |  |      |                 |
| 200 V<br>208 V                       |  | HP   | 25              |
| 230 V<br>240 V                       |  | HP   | 40              |
| 460 V<br>480 V                       |  | HP   | 75              |
| 575 V<br>600 V                       |  | HP   | 100             |
| Single-phase                         |  |      |                 |
| 115 V<br>120 V                       |  | HP   | 7.5             |
| 230 V<br>240 V                       |  | HP   | 15              |
| General use                          |  | A    | 125             |
| Short Circuit Current Rating         |  | SCCR |                 |
| Basic Rating                         |  |      |                 |
| SCCR                                 |  | kA   | 10              |
| max. Fuse                            |  | A    | 600             |
| max. CB                              |  | A    | 600             |
| 480 V High Fault                     |  |      |                 |
| SCCR (fuse)                          |  | kA   | 30/100          |
| max. Fuse                            |  | A    | 300/300 Class J |
| SCCR (CB)                            |  | kA   | 65              |
| max. CB                              |  | A    | 250             |
| 600 V High Fault                     |  |      |                 |
| SCCR (fuse)                          |  | kA   | 30/100          |
| max. Fuse                            |  | A    | 300/300 Class J |
| SCCR (CB)                            |  | kA   | 30              |
| max. CB                              |  | A    | 350             |
| Special Purpose Ratings              |  |      |                 |
| Electrical Discharge Lamps (Ballast) |  |      |                 |
| 480V 60Hz 3phase, 277V 60Hz 1phase   |  | A    | 100             |
| 600V 60Hz 3phase, 347V 60Hz 1phase   |  | A    | 100             |
| Incandescent Lamps (Tungsten)        |  |      |                 |
| 480V 60Hz 3phase, 277V 60Hz 1phase   |  | A    | 100             |
| 600V 60Hz 3phase, 347V 60Hz 1phase   |  | A    | 100             |
| Resistance Air Heating               |  |      |                 |
| 480V 60Hz 3phase, 277V 60Hz 1phase   |  | A    | 110             |
| 600V 60Hz 3phase, 347V 60Hz 1phase   |  | A    | 110             |
| Refrigeration Control (CSA only)     |  |      |                 |
| LRA 480V 60Hz 3phase                 |  | A    | 540             |
| FLA 480V 60Hz 3phase                 |  | A    | 90              |
| LRA 600V 60Hz 3phase                 |  | A    | 420             |
| FLA 600V 60Hz 3phase                 |  | A    | 70              |
| Elevator Control                     |  |      |                 |
| 200V 60Hz 3phase                     |  | HP   | 20              |
| 200V 60Hz 3phase                     |  | A    | 62.1            |
| 240V 60Hz 3phase                     |  | HP   | 30              |

|                  |    |    |
|------------------|----|----|
| 240V 60Hz 3phase | A  | 80 |
| 480V 60Hz 3phase | HP | 60 |
| 480V 60Hz 3phase | A  | 77 |
| 600V 60Hz 3phase | HP | 75 |
| 600V 60Hz 3phase | A  | 77 |

### Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                                                                                                                  |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 160                                                                                                                              |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 12.1                                                                                                                             |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 36.3                                                                                                                             |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 2.3                                                                                                                              |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                                                |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                                                                                                              |
| Operating ambient temperature max.                                                                                     |                   | °C | 60                                                                                                                               |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                                                  |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                                                  |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                                                                                 |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                                                                                             |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                                                                                    |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                                                                              |                   |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

### Technical data ETIM 8.0

|                                                                                                                                                                                       |    |           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----------|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)                                                                                               |    |           |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015]) |    |           |
| Rated control supply voltage Us at AC 50HZ                                                                                                                                            | V  | 100 - 120 |
| Rated control supply voltage Us at AC 60HZ                                                                                                                                            | V  | 100 - 120 |
| Rated control supply voltage Us at DC                                                                                                                                                 | V  | 0 - 0     |
| Voltage type for actuating                                                                                                                                                            |    | AC        |
| Rated operation current Ie at AC-1, 400 V                                                                                                                                             | A  | 160       |
| Rated operation current Ie at AC-3, 400 V                                                                                                                                             | A  | 95        |
| Rated operation power at AC-3, 400 V                                                                                                                                                  | kW | 45        |
| Rated operation current Ie at AC-4, 400 V                                                                                                                                             | A  | 65        |
| Rated operation power at AC-4, 400 V                                                                                                                                                  | kW | 33        |

|                                                         |  |    |                  |
|---------------------------------------------------------|--|----|------------------|
| Rated operation power NEMA                              |  | kW | 55               |
| Modular version                                         |  |    | No               |
| Number of auxiliary contacts as normally open contact   |  |    | 0                |
| Number of auxiliary contacts as normally closed contact |  |    | 0                |
| Type of electrical connection of main circuit           |  |    | Screw connection |
| Number of normally closed contacts as main contact      |  |    | 0                |
| Number of normally open contacts as main contact        |  |    | 4                |