

Flush-mounting door frame with sheet steel door and three-point turn-lock for 3-component system, W = 600 mm, H = 460 mm



Part no. BP-U-3S-600/4

Catalog No. 111153

EL-Nummer (Norway) 2459605

Delivery program

| | | | |
|----------------------|--|----|-----------------------|
| Mounting type | | | Flush mounted |
| Material | | | Sheet steel |
| Door interlock | | | Three-point turn-lock |
| Degree of Protection | | | IP30 |
| Surface finish | | | With powder coating |
| Width | | mm | 600 |
| Height | | mm | 460 |
| Suitable for height | | mm | 460 |
| Suitable for width | | mm | 600 |
| Colour | | | light gray (RAL 7035) |

Technical data ETIM 8.0

| | | | |
|---|--|----|----------------|
| Cabinet enclosures (EG000011) / Door/operating panel (enclosure/cabinet) (EC000747) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss10.0.1-27-18-22-04 [ACN614011]) | | | |
| Model | | | Lock door |
| Version as glazed door | | | No |
| Version as door for disconnecting switch interlocking | | | No |
| Width | | mm | 635 |
| Height | | mm | 465 |
| Depth | | mm | 70 |
| EMC-version | | | Yes |
| Material | | | Steel |
| Surface finishing | | | Powder coating |
| Colour | | | Grey |
| Degree of protection (IP) | | | IP30 |
| Degree of protection (NEMA) | | | Other |