

Switch disconnector, low voltage, 160 A, AC 690 V, NH00, AC23B, 3P, IEC



Powering Business Worldwide™

Part no.

SIZE 00 HOR FSD - 60MM BUS:M8 SCREWS BTM
EBH0013TBM8**General specifications**

Product name	Eaton Bussmann series low voltage NH fuse base
Part no.	SIZE 00 HOR FSD - 60MM BUS:M8 SCREWS BTM
EAN	5027590336253
Product Length/Depth	210 millimetre
Product height	140 millimetre
Product width	110 millimetre
Product weight	999 gram
Compliances	CE
Certifications	IEC 60947-3 IEC/EN 60947-1
Product Tradename	None
Product Type	Low voltage NH fuse base
Product Sub Type	None

Electrical data

Amperage Rating	160 A
Voltage rating	690

Product specifications

Number of poles	Three-pole
Mounting method	DIN rail 60 mm busbar mounting

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss10.0.1-27-37-14-01 [AKF058013])

Version as main switch	No
Version as safety switch	No
Max. rated operation voltage Ue AC	V 690
Rated permanent current Iu	A 160
Rated operation power at AC-23, 400 V	kW 0.064
Conditioned rated short-circuit current Iq	kA 0.08
Rated short-time withstand current Icw	kA 80
Suitable for fuses	NH00
Number of poles	3
With error protection	No
Type of electrical connection of main circuit	Screw connection
Cable entry	Other
Equipped with connectors	No
Suitable for floor mounting	No
Suitable for front mounting	No
Suitable for busbar mounting	Yes
Type of control element	Cover grip
Position control element	Front side
Motor drive optional	No
Motor drive integrated	No
Version as emergency stop installation	No
Degree of protection (IP), front side	IP30