

Phase sequence relays, 200 - 500 V AC, 50/60 Hz



Powering Business Worldwide™

Part no.	EMR6-F500-G-1
Catalog No.	184789
Alternate Catalog No.	EMR6-F500-G-1
EL-Nummer	4101985
(Norway)	

Delivery program

Product range			EMR Measuring and monitoring relays
Basic function			Phase sequence relays
			Monitoring of three-phase networks Phase failure detection at $< 0.6 \times U_e$ Power supply from the measuring circuit Fixed response delay
Monitoring voltage per phase	U _N	V AC	200 - 500 V AC, 50/60 Hz
Monitoring of			Phase failure Phase sequence
Supply voltage			200 - 500 V AC, 50/60 Hz
Width		mm	22.5

Technical data

General

Standards			IEC/EN 60255-6,
Lifespan, mechanical	Operations	$\times 10^6$	30
Climatic proofing			Damp heat, cyclical to IEC 60068-2-30: 24 h cycle, 55° C, 93% relative humidity, 96 h
Ambient temperature			
Operation		°C	
Operating ambient temperature min.		°C	-20
Operating ambient temperature max.		°C	+ 60
Storage		°C	- 40 - 85
Mounting position			As required
Shock resistance			Class 2
Degree of protection			
Terminals			IP20
Enclosures			IP50
Terminal capacities		mm ²	
Solid		mm ²	2 x 2.5
Flexible with ferrule		mm ²	2 x 2.5/2 x AWG14
Standard screwdriver		mm	5.5 x 0.8
Tightening torque		Nm	0.5 - 0.8
Fixing			Snap fixing, top-hat rail IEC/EN 60715
MTBF (mean time between failures)			628571 h

Contacts

Rated impulse withstand voltage	U _{imp}	V AC	4000
Oversupply category/pollution degree			III/3

Power supply

Supply voltage			200 - 500 V AC, 50/60 Hz
Voltage tolerance		$\times U_c$	0.85 - 1.1
Power consumption		VA	11
Rated frequency	f	Hz	50 - 60
Duty factor		% DF	100

Measuring circuits

Monitoring voltage	U _n	V AC	
Monitoring voltage, min.		V AC	200
Monitoring voltage, max.		V AC	500

Frequency	Hz	
Min. frequency range	Hz	50
Max. frequency range	Hz	60
Frequency	Hz	50 - 60
Frequency	Hz	50 - 60
Measuring cycle	ms	500
Temperature error	%/°C	0.06
Error within supply voltage	%	0.5

Status indication

Output relay energized		LED, yellow
Status indicator (LED)		Red, solid: Phase failure Red, flashing: Phase sequence fault

Relay output contacts

Rated operational voltage	U _e	V AC	500
Rated operational current	I _e	A	
AC-12 at 230 V	I _e	A	4
AC-15 with 230 V	I _e	A	3
DC-12 at 24 V	I _e	A	4
DC-13 at 24 V	I _e	A	2
Minimum Switching capacity			10 mA / 24 V
Lifespan, electrical (AC-12/230 V/4 A)	Operations	$\times 10^6$	
Lifespan, electrical	Operations	$\times 10^6$	0.3
Short-circuit rating			
max. fuse	Fast/gL	A	10

Electromagnetic compatibility (EMC)

Electromagnetic compatibility			IEC/EN 60947-6-2
ESD	Air/contact discharge	kV	IEC/EN 61000-4-2 level 3
HF-immunity to radiation			IEC/EN 61000-4-3 level 3
Burst			IEC/EN 61000-4-4 level 3
Surge			IEC/EN 61000-4-5 Level 4
HF-immunity to line-conducted interference			IEC/EN 61000-4-6 level 3

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-20
Operating ambient temperature max.		°C	60

Technical data ETIM 8.0

Relays (EG000019) / Phase monitoring relay (EC001441)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Monitoring equipment (low-voltage switch technology) / Asymmetry monitoring equipment (ecl@ss10.0.1-27-37-18-03 [AKF097014])			
Type of electric connection			Screw connection
With detachable clamps			No
Rated control supply voltage Us at AC 50Hz		V	200 - 500
Rated control supply voltage Us at AC 60Hz		V	200 - 500
Rated control supply voltage Us at DC		V	0 - 0
Voltage type for actuating			AC
Phase sequence monitoring			Yes
Phase failure detection			Yes
Function under voltage detection			No
Function over voltage detection			No
Phase imbalance monitoring			No
Voltage measuring range		V	200 - 500
Min. adjustable delay-on energization time		s	0
Max. permitted delay-on energization time		s	0

Min. adjustable off-delay time	s	0
Max. permitted off-delay time	s	0
Number of contacts as normally closed contact		0
Number of contacts as normally open contact		0
Number of contacts as change-over contact		2
Width	mm	22.5
Height	mm	85.6
Depth	mm	103.7