

## Miniature circuit breaker (MCB), 3 A, 2p, characteristic: C, DC



**Part no.** FAZ-C3/2-DC  
**Catalog No.** 279135  
**Alternate Catalog No.** FAZ-C3/2-DC  
**EL-Nummer (Norway)** 1691501

Similar to illustration

## Delivery program

|                                                 |          |    |                                |
|-------------------------------------------------|----------|----|--------------------------------|
| Basic function                                  |          |    | Miniature circuit-breakers     |
| Number of poles                                 |          |    | 2 pole                         |
| Tripping characteristic                         |          |    | C                              |
| Application                                     |          |    | Switchgear for DC applications |
| Rated current                                   | $I_n$    | A  | 3                              |
| Rated switching capacity acc. to IEC/EN 60947-2 | $I_{cu}$ | kA | 10                             |
| Product range                                   |          |    | FAZ-DC                         |

## Technical data

## Electrical

|                                                 |            |         |                       |
|-------------------------------------------------|------------|---------|-----------------------|
| Standards                                       |            |         | EN 45545-2; IEC 61373 |
| Rated operational voltage                       | $U_e$      | V       |                       |
|                                                 |            | V DC    | 250 (per pole)        |
| Rated switching capacity acc. to IEC/EN 60947-2 | $I_{cu}$   | kA      | 10                    |
| Characteristic                                  |            |         | C                     |
| Max. back-up fuse                               |            | A gL/gG | 100                   |
| Selectivity Class                               |            |         | 3                     |
| lifespan                                        |            |         |                       |
| Lifespan                                        | Operations |         | > 10000               |
| Direction of incoming supply                    |            |         | Polarity dependent    |

## Mechanical

|                              |  |                 |                                         |
|------------------------------|--|-----------------|-----------------------------------------|
| Standard front dimension     |  | mm              | 45                                      |
| Enclosure height             |  | mm              | 80                                      |
| Mounting width per pole      |  | mm              | 17.5                                    |
| Mounting                     |  |                 | IEC/EN 60715 top-hat rail               |
| Degree of Protection         |  |                 | IP20, IP40 (when fitted)                |
| Terminals top and bottom     |  |                 | Twin-purpose terminals                  |
| Terminal protection          |  |                 | Finger and back-of-hand proof to BGV A2 |
| Terminal capacities          |  | mm <sup>2</sup> |                                         |
|                              |  | mm <sup>2</sup> | 1 x 25                                  |
|                              |  | mm <sup>2</sup> | 2 x 10                                  |
| Thickness of busbar material |  | mm              | 0.8 ... 2                               |
| Mounting position            |  |                 | As required                             |

## Design verification as per IEC/EN 61439

|                                                          |            |   |     |
|----------------------------------------------------------|------------|---|-----|
| Technical data for design verification                   |            |   |     |
| Rated operational current for specified heat dissipation | $I_n$      | A | 3   |
| Heat dissipation per pole, current-dependent             | $P_{vid}$  | W | 0   |
| Equipment heat dissipation, current-dependent            | $P_{vid}$  | W | 2.4 |
| Static heat dissipation, non-current-dependent           | $P_{vs}$   | W | 0   |
| Heat dissipation capacity                                | $P_{diss}$ | W | 0   |

|                                    |    |                                                                             |
|------------------------------------|----|-----------------------------------------------------------------------------|
| Operating ambient temperature min. | °C | -40                                                                         |
| Operating ambient temperature max. | °C | 75                                                                          |
|                                    |    | linear, per +1 °C, results in a 0.5% reduction of current carrying capacity |

## Technical data ETIM 8.0

|                                                                                                                                                                                                                      |                 |          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)                                                                                                                                   |                 |          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB)<br>(ec1@ss10.0.1-27-14-19-01 [AAB905014]) |                 |          |
| Built-in depth                                                                                                                                                                                                       | mm              | 70.5     |
| Release characteristic                                                                                                                                                                                               |                 | C        |
| Number of poles (total)                                                                                                                                                                                              |                 | 2        |
| Number of protected poles                                                                                                                                                                                            |                 | 2        |
| Rated current                                                                                                                                                                                                        | A               | 3        |
| Rated voltage                                                                                                                                                                                                        | V               | 250      |
| Rated insulation voltage Ui                                                                                                                                                                                          | V               | 440      |
| Rated impulse withstand voltage Uimp                                                                                                                                                                                 | kV              | 4        |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V                                                                                                                                             | kA              | 0        |
| Voltage type                                                                                                                                                                                                         |                 | DC       |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V                                                                                                                                             | kA              | 0        |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V                                                                                                                                          | kA              | 10       |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V                                                                                                                                          | kA              | 10       |
| Frequency                                                                                                                                                                                                            | Hz              | 50 - 60  |
| Current limiting class                                                                                                                                                                                               |                 | 3        |
| Flush-mounted installation                                                                                                                                                                                           |                 | No       |
| Concurrently switching neutral conductor                                                                                                                                                                             |                 | No       |
| Over voltage category                                                                                                                                                                                                |                 | 3        |
| Pollution degree                                                                                                                                                                                                     |                 | 2        |
| Additional equipment possible                                                                                                                                                                                        |                 | Yes      |
| Width in number of modular spacings                                                                                                                                                                                  |                 | 2        |
| Degree of protection (IP)                                                                                                                                                                                            |                 | IP20     |
| Ambient temperature during operating                                                                                                                                                                                 | °C              | -25 - 75 |
| Connectable conductor cross section multi-wired                                                                                                                                                                      | mm <sup>2</sup> | 1 - 25   |
| Connectable conductor cross section solid-core                                                                                                                                                                       | mm <sup>2</sup> | 1 - 25   |
| Explosion-proof                                                                                                                                                                                                      |                 | No       |