



## CABLE TIES GT - natural

material: polyamide 6.6

installation temp. : -10°C to +60°C

working temp. : -40°C to +85°C

dielectric resistance: 50kV/mm<sup>2</sup>

humidity absorption: 2,5% (50% R.H., +23°C)

flammability to raw material: UL-94 V2

tolerance: ±5%

TYPE	DIMENSIONS [mm]	max/min BUNDLE DIAMETER [mm]	TENSILE STRENGTH [kg]	PACKAGE [pcs]	<input type="checkbox"/>
GT-100MCS	100x1,9	20/3	8	100	<input type="checkbox"/>
GT-100MC	100x2,5	20/3	8	100	<input type="checkbox"/>
GT-120MC	120x2,5	27/3	8	100	<input type="checkbox"/>
GT-140MC	140x2,5	33/3	8	100	<input type="checkbox"/>
GT-160MC	160x2,5	43/3	8	100	<input type="checkbox"/>
GT-200MC	200x2,5	52/3	8	100	<input type="checkbox"/>
GT-120IC	120x3,2	28/3	18	100	<input type="checkbox"/>
GT-140IC	140x3,6	33/3	18	100	<input type="checkbox"/>
GT-150IC	150x3,6	36/3	18	100	<input type="checkbox"/>
GT-200IC	200x3,6	52/3	18	100	<input type="checkbox"/>
GT-250IC	250x3,6	68/3	18	100	<input type="checkbox"/>
GT-300IC	280x3,6	78/3	18	100	<input type="checkbox"/>
GT-370IC	368x3,6	105/3	18	100	<input type="checkbox"/>
GT-120STC	120x4,6	24/3	22	100	<input type="checkbox"/>
GT-160STC	160x4,8	36/3	22	100	<input type="checkbox"/>
GT-190STC	190x4,8	49/3	22	100	<input type="checkbox"/>
GT-250STC	250x4,5	68/3	22	100	<input type="checkbox"/>
GT-300STC	300x4,8	81/3	22	100	<input type="checkbox"/>
GT-370STC	368x4,8	100/3	22	100	<input type="checkbox"/>
GT-430STC	430x4,8	122/3	22	100	<input type="checkbox"/>
GT-500STC	500x4,8	154/3	22	100	<input type="checkbox"/>
GT-740STC	740x4,8	219/3	22	100	<input type="checkbox"/>
GT-200HD	200x7,6	50/8	55	100	<input type="checkbox"/>
GT-300HD	300x7,6	80/8	55	100	<input type="checkbox"/>
GT-370HD	370x7,6	101/8	55	100	<input type="checkbox"/>
GT-430HD	450x7,6	128/8	55	100	<input type="checkbox"/>
GT-530HD	540x7,6	159/8	55	100	<input type="checkbox"/>
GT-770HDL	780x8,8	227/8	80	100	<input type="checkbox"/>
GT-830HDL	812x9,0	243/8	80	100	<input type="checkbox"/>
GT-1170HDL	1220x9,0	372/8	80	100	<input type="checkbox"/>