

H05V-U / (H)05V-U / (H)07V-U

przewody jednożyłowe w izolacji PVC, żyła jednodrutowa zgodna z VDE



			Numer katalogowy							
ca. RAL→			9005		5015	8003	3000	9003	7001	4005
Przekrój mm²	średnica zewn. min.-max w mm	Waga Cu kg/km	czarny	żółto-zielony	niebieski	brązowy	czerwony	biały	szary	fioletowy
 Zwój w opakowaniu papierowym (100 m)										
H05 V-U										
0,5	1,9 - 2,3	4,8	28761	28762	28763	28764	28765	28766	28767	28768
0,75	2,1 - 2,5	7,2	28769	28770	28771	28772	28773	28774	28775	28776
1	2,2 - 2,7	9,6	28777	28778	28779	28780	28781	28782	28783	28784
 Szpuła (różna pojemność)										
H05 V-U										
0,5	1,9 - 2,3	4,8	26937	26938	26939	26940	26941	26942	26943	26944
0,75	2,1 - 2,5	7,2	26945	26946	26947	26948	26949	26950	26951	26952
1	2,2 - 2,7	9,6	26953	26954	26955	26956	26957	26958	26959	26960
 Zwój w opakowaniu papierowym (100 m)										
H07 V-U										
1,5	2,6 - 3,2	14,4	28785	28786	28787	28788	28789	28790	28791	28792
2,5	3,2 - 3,9	24,0	28793	28794	28795	28796	28797	28798	28799	28800
4	3,6 - 4,4	38,0	28801	28802	28803	28804	28805	28806	28807	28808
6	4,1 - 5,0	58,0	28809	28810	28811	28812	28813	28814	28815	28816
10	5,3 - 6,4	96,0	28817	28818	28819	28820	28821	28822	28823	28824
 Bęben										
H07 V-U										
1,5	2,6 - 3,2	14,4	28145	28146	28147	28148	28149	28150	28151	28152
2,5	3,2 - 3,9	24,0	28153	28154	28155	28156	28157	28158	28159	28160
4	3,6 - 4,4	38,0	28161	28162	28163	28164	28165	28166	28167	28168
6	4,1 - 5,0	58,0	28169	28170	28171	28172	28173	28174	28175	28176
10	5,3 - 6,4	96,0	28177	28178	28179	28180	28181	28182	28183	28184

Wymiary oraz dane techniczne mogą ulec zmianie bez uprzedzenia.