

## Main switch, 63A, 3 p

Part no. HIS-63/3  
Catalog No. 142822

Similar to illustration

## Technical data ETIM 8.0

|                                                                                                                                                                                                                                                  |  |    |                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------|
| Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)                                                                                                                                      |  |    |                 |
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss10.0.1-27-14-23-01 [AFZ813014]) |  |    |                 |
| Switching function                                                                                                                                                                                                                               |  |    | Off switch      |
| Number of contacts as normally open contact                                                                                                                                                                                                      |  |    | 0               |
| Number of contacts as normally closed contact                                                                                                                                                                                                    |  |    | 0               |
| Number of contacts as change-over contact                                                                                                                                                                                                        |  |    | 0               |
| Number of poles                                                                                                                                                                                                                                  |  |    | 3               |
| Rated current                                                                                                                                                                                                                                    |  | A  | 63              |
| Rated voltage                                                                                                                                                                                                                                    |  | V  | 240             |
| Min. rated voltage                                                                                                                                                                                                                               |  | V  | 240             |
| Rated switching capacity                                                                                                                                                                                                                         |  | kA | 0               |
| Short-circuit breaking capacity (Icw)                                                                                                                                                                                                            |  | kA | 2               |
| Voltage type                                                                                                                                                                                                                                     |  |    | AC              |
| With signal lamp                                                                                                                                                                                                                                 |  |    | No              |
| Colour calotte                                                                                                                                                                                                                                   |  |    | Other           |
| Lamp type                                                                                                                                                                                                                                        |  |    | Other           |
| Lamp socket                                                                                                                                                                                                                                      |  |    | Other           |
| Max. lamp power                                                                                                                                                                                                                                  |  | W  | 0               |
| Width in number of modular spacings                                                                                                                                                                                                              |  |    | 3               |
| Built-in depth                                                                                                                                                                                                                                   |  | mm | 69.5            |
| Degree of protection (IP)                                                                                                                                                                                                                        |  |    | IP20            |
| Imprint/indication                                                                                                                                                                                                                               |  |    | Symbol "arrows" |
| Forced segregation (according to DIN VDE 0113)                                                                                                                                                                                                   |  |    | No              |