

Busbar system, accessories Busbar center-to-center spacing 40 mm Busbar support 3-pole 12x 5, 2x12x 5.15x 5, 2x15x 5 as end and intermediate holder incl. inlay components for Busbar thickness 5 mm and incl. end covers



Figure similar

Model	
product brand name	SETRON
product designation	busbar support
operating voltage at AC rated value	690 V
type of connectable conductor cross-sections for copper conductor stranded	12 mm x 5 mm - 15 mm x 10 mm

Mechanical Design	
busbar center-to-center spacing	40 mm

Approvals Certificates		
General Product Approval	Test Certificates	Marine / Shipping



[Confirmation](#)



[Miscellaneous](#)



Marine / Shipping	other	Environment	
-------------------	-------	-------------	--



[Miscellaneous](#)


[Confirmation](#)

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1903-3AB00>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/8US1903-3AB00>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1903-3AB00
- CAX-Online-Generator
<http://www.siemens.com/cax>
- Tender specifications
<http://www.siemens.com/specifications>



last modified:

7/28/2022 

