

PRODUCT-DETAILS

KSB-113C

KSB-113C Signal Beacon



General Information

Extended Product Type	KSB-113C
Product ID	1SFA616080R1138
EAN	7320500202715
Catalog Description	KSB-113C Signal Beacon
Long Description	KSB-113C Light Element Xenon tube Clear Flashing light

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369001
Product Main Type	KSB

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.075 m
Product Net Depth /	0.097 m

Length	
Product Net Height	0.075 m
Product Net Weight	0.14 kg

Technical

Accessory Type	Signal towers and beacons
Color	Clear
Enclosure Type NEMA	Type5
Function	Flashing light
Lamp Type	Xenon tube
Rated Control Supply Voltage (Us)	115 V AC
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	115 V AC
Standards	CAN/CSA C22.2 No.14, IEC/EN 60947-1, IEC/EN 60947-5-1, UL 508

Environmental

Ambient Air Temperature	Operation -20 ... +50 °C Storage -20 ... 50 °C
Degree of Protection	Front IP65
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Information	2CMT2015-005456
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMT2015-005456
Environmental Information	1SFC151006D0201
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005456

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.1 m
Package Level 1 Depth / Length	0.08 m
Package Level 1 Height	0.075 m
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	7320500202715

Classifications

eClass	V11.0 : 27143210
E-Number (Finland)	2313588
E-Number (Sweden)	5378424
ETIM 6	EC001042 - Signal tower complete
ETIM 7	EC001334 - Continuous luminaire

ETIM 8	EC001334 - Continuous luminaire
Object Classification Code	P
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Signal Towers and Beacons

