

PRODUCT-DETAILS

KSB-203G

KSB-203G Signal Beacon



General Information

Extended Product Type	KSB-203G
Product ID	1SFA616080R2032
EAN	7320500202784
Catalog Description	KSB-203G Signal Beacon
Long Description	KSB-203G Light Element Xenon tube Green Flashing light

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369001
Product Main Type	KSB

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.075 m
Product Net Depth /	0.097 m

Length

Product Net Height	0.075 m
Product Net Weight	0.15 kg

Technical

Accessory Type	Signal towers and beacons
Color	Green
Enclosure Type NEMA	Type5
Function	Flashing light
Lamp Type	Xenon tube
Rated Control Supply Voltage (U _s)	24 V DC
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 V DC
Standards	CAN/CSA C22.2 No.14, IEC/EN 60947-1, IEC/EN 60947-5-1, UL 508

Environmental

Ambient Air Temperature	Operation -20 ... +50 °C Storage -20 ... 50 °C
Degree of Protection	Front IP65
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Information	2CMT2015-005456
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMT2015-005456
Environmental Information	1SFC151006D0201
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005456

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.1 m
Package Level 1 Depth / Length	0.08 m
Package Level 1 Height	0.075 m
Package Level 1 Gross Weight	0.15 kg
Package Level 1 EAN	7320500202784

Classifications

eClass	V11.0 : 27143210
E-Number (Finland)	2313596
E-Number (Sweden)	5378408
ETIM 6	EC001042 - Signal tower complete
ETIM 7	EC001334 - Continuous luminaire

ETIM 8	EC001334 - Continuous luminaire
Object Classification Code	P
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Signal Towers and Beacons

