

Combination of contact element and self-monitoring contact element  
M22-K01SMC10, M22-A mounting adapter, and M22-XSMC signaling  
contact actuator., 3 NC



Part no. M22-AFK03SMC10  
Catalog No. 180794  
Alternate Catalog No. M22-AFK03SMC10  
EL-Nummer 4315745  
(Norway)

**Delivery program**

Basic function accessories			Self-monitoring contact elements
Description			Combination of contact element and self-monitoring contact element M22-K01SMC10, M22-A mounting adapter, and M22-XSMC signaling contact actuator. The N/O in the self-monitoring contact element is actuated when mounted with M22-XSMC. Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany
Connection technique			Cage Clamp, Push-in
Fixing			Front fixing
Degree of Protection			IP20
Connection to SmartWire-DT			no
<b>Contacts</b>			
N/C = Normally closed			3 NC
Notes			= safety function, by positive opening to IEC/EN 60947-5-1
<b>Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1</b>			
	mm		5.5
Maximum travel	mm		5.8
Minimum force for positive opening	N		60
Connection technique			Cage Clamp, Push-in

**Technical data**

**General**

Standards			IEC 60947-5-1
Lifespan, mechanical	Operations	$\times 10^6$	> 1
Operating frequency	Operations/h		$\leq 3600$
Actuating force		n	$\leq 13.5$
Degree of Protection			IP20
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 Dry heat to IEC 60068-2-2
Ambient temperature			
Open		°C	-25 - +70
Storage		°C	- 40 - + 85
Mechanical shock resistance to IEC 60068-2-27 Shock duration 11 ms, half-sinusoidal		g	> 50
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	2 x 1 (0.2 - 1.5) 2 x 1 (0.75 - 1.5) Can be plugged without tools
Flexible with ferrule		mm <sup>2</sup>	2 x 1 (0.25 - 1) Use WAGO Variocrimp 4 crimping tool; please enquire for others
Solid or stranded		AWG	2 x 1 (24 - 16)

**Contacts**

Rated impulse withstand voltage	$U_{imp}$	V AC	4000
Rated insulation voltage	$U_i$	V	250
Overvoltage category/pollution degree			III/3
Max. short-circuit protective device			

Fuseless		Type	FAZ-B4
Fuse	gG/gL	A	4
<b>Switching capacity</b>			
Rated operational current	$I_e$	A	
AC-15			
24 V	$I_e$	A	4
60 V	$I_e$	A	4
230 V	$I_e$	A	1.5
DC-13			
24 V	$I_e$	A	1.5
60 V	$I_e$	A	0.8
110 V	$I_e$	A	0.4
220 V	$I_e$	A	0.2
<b>Auxiliary contacts</b>			
Rated conditional short-circuit current	$I_q$	kA	1

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss10.0.1-27-37-13-02 [AKN342013])			
Number of contacts as change-over contact			0
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			0
Number of fault-signal switches			0
Rated operation current $I_e$ at AC-15, 230 V		A	1.5
Type of electric connection			Spring clamp connection
Model			Top mounting
Mounting method			Front fastening
Lamp holder			None