

**Illuminated pushbutton actuator, RMQ-Titan, flat, momentary, White,  
blank, Front ring stainless steel**

**Part no. M30I-FDL-W  
188058**

<b>General specifications</b>	
Product name	Eaton Moeller® series M30 Illuminated pushbutton actuator
Part no.	M30I-FDL-W
EAN	4015081857371
Product Length/Depth	36 millimetre
Product height	30 millimetre
Product width	46 millimetre
Product weight	0.041 kilogram
Certifications	IEC/EN 60947 VDE 0660 IEC/EN 60947-5 UL Listed GL CSA-C22.2 No. 14-05 and 94-M91 UL 508 DNV UL File No.: E29184 CSA File No.: 012528 CE marking CSA Class No.: 3211-03 UL Category Control No.: NKCR CSA certified
Product Tradename	M30
Product Type	Illuminated pushbutton actuator
Product Sub Type	None
<b>Features &amp; Functions</b>	
Bezel color	Stainless steel
Bezel material	Metal
Design	Flat Flat front
Fitted with:	Front ring
Inscription	Blank
<b>General information</b>	
Degree of protection	IP69 IP66 IP67
Degree of protection (front side)	IP67 NEMA 4X, 13
Lifespan, mechanical	5,000,000 Operations
Opening diameter	30.5 mm
Operating frequency	3600 Operations/h
Product category	RMQ-Titan
Size	Front dimensions: Ø 36 mm
Suitable for	Illumination
Type	Illuminated pushbutton actuator
<b>Ambient conditions, mechanical</b>	
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>Communication</b>	

Connection to SmartWire-DT			With SWD-RMQ connections Yes
<b>Actuator</b>			
Actuating force			5 N
Actuator color			White
Actuator function			Momentary Spring-return
<b>Contacts</b>			
Force for positive opening - min			0 N

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014])			
Colour button			White
Number of command positions			1
Construction type lens			Round
Hole diameter		mm	30.5
Width opening		mm	0
Height opening		mm	0
Type of button			Flat
Suitable for illumination			Yes
With protective cover			No
Labelled			No
Switching function latching			No
Spring-return			Yes
With front ring			Yes
Material front ring			Metal
Colour front ring			Stainless steel
Degree of protection (IP), front side			IP67
Degree of protection (NEMA), front side			4X, 13