

PHILIPS**Lighting**

MASTER VALUE LEDspot PAR

MAS LEDspot VLE D 6-50W 927 PAR20 40D

With its robust design and warm-white beam of light, these new-generation PAR lamps are ideal for general lighting and spot lighting in the hospitality industry. It's a dimmable solution. They are especially suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. The product offers more energy saving comparing with normal LED spots.

Product data

General Information	
Cap-Base	E27
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Narrow Cone
EU RoHS compliant	Yes
Light Technical	
Color Code	927 [CCT of 2700K]
Beam Angle (Nom)	40 degree(s)
Luminous Flux	500 lm
Luminous Intensity (Nom)	1,000 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	83 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	500 lm
Operating and Electrical	
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Photobiological safety according to EN 62471	RG1
Temperature	
T-Case Maximum (Nom)	80 °C

MASTER VALUE LEDspot PAR

Controls and Dimming

Dimmable	Only with specific dimmers
----------	----------------------------

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	PAR20


Approval and Application

Energy Efficiency Class	F
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	6 kWh
EPREL Registration Number	1121748
EyeComfort	Yes

Product Data


Order product name	MAS LEDspot VLE D 6-50W 927 PAR20 40D
Full product name	MAS LEDspot VLE D 6-50W 927 PAR20 40D
Full product code	871951444310500
Order code	929003486002
Material Nr. (12NC)	929003486002
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514443105
Numerator - Packs per outer box	6
EAN/UPC - Case	8719514443112

Dimensional drawing




Product	D	C
MAS LEDspot VLE D 6-50W 927 PAR20 40D	65 mm	85 mm

Photometric data




Accent Lighting Spots - MAS LEDspot VLE D 6-50W 927 PAR20 40D



Spectral Power Distribution Colour - MAS LEDspot VLE D 6-50W 927 PAR20 40D


MASTER VALUE LEDspot PAR

Photometric data




Light Distribution Diagram - MAS LEDspot VLE D 6-50W 927 PAR20 40D

Lifetime



Life Expectancy Diagram - MAS LEDspot VLE D 6-50W 927 PAR20 40D



Lumen Maintenance Diagram - MAS LEDspot VLE D 6-50W 927 PAR20 40D

