


## Pressure switches with auxiliary contacts, 25 bar, 1 changeover contact, IP65

Part no.	MCS22
Catalog No.	098019
Alternate Catalog No.	MCS22
EL-Nummer (Norway)	4356107

## Delivery program

Note on use	This product complies with Low-Voltage Directive 2014/35/EC and EMC Directive 2014/30/EC and meets the requirements in EN 60947-5-1. This product does not meet the rail industry's standard requirements. Accordingly, the user must review it separately for the specific application at hand.	
Product range	Pressure switches with auxiliary contacts	
Degree of Protection	IP65	
Contacts	1 changeover contact	
<b>Cut-in pressure and cut-out pressure: separate stepless adjustment.</b> <b>All the intersection points within the diagram area can be set.</b>		
		Min. switching differential: 0.7 bar
		Example:
		Cut-out pressure 17.5 bar
		Cut-in pressure 7.8 bar
		Variable switching differential
Max. operating pressure	bar	25

## Notes



## Features:

- Pressure pipe flange R 1/4"
- If required: pressure pipe flange R 1/2"
- IP65 in conjunction with V-M20 cable gland
- 1 Insulated protective conductor terminal (GND)
- 2 cable entry knockouts for M20
- Neoprene membrane, resistant to aging, air, engine oil, and water min. -25 °C, max. +80 °C

Cut-in and cut-out pressures are factory-preset as specified with type suffix: →#203948

R 1/4" corresponds to G 1/4

R 1/2" corresponds to G 1/2 according to ISO 228-1

Auxiliary contact to IEC/EN 60947-1

## Technical data

## General

Standards		IEC/EN 60947-5-1
Test pressure	bar	32
Rupturing pressure	bar	90
Operating frequency	Operations/h	≤ 1500
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature		-25 - 70
Degree of Protection		IP65
Mounting position		Vertical

			90° in all directions
Mechanical shock resistance to IEC 60068-2-27	Half-sinusoidal shock 20 ms	g	> 18
Vibration resistance acc. to IEC/EN 60068-2-6	Amplitude 1 mm	Hz	36
lifespan	Operations	$\times 10^6$	1
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	1 x (0.75 - 2.5) 2 x (0.75 - 1.5)
Flexible with ferrules to DIN 46228		mm <sup>2</sup>	1 x (0.5 - 1.5)
Terminations			Tunnel terminal
Terminal screw			M3
Tightening torque of terminal screw		Nm	0.5

### Contacts/switching capacity

Rated impulse withstand voltage	U <sub>imp</sub>	V AC	4000
Rated insulation voltage	U <sub>i</sub>	V	400
Overvoltage category/pollution degree			III/3
Max. short-circuit protective device			
Fuseless		Type	PKZM0-6,3
Fuse	gG/gL	A	10
AC-15			
Rated operational current			
230 V, 50/60Hz		A	2
DC-13			
Rated operational current			
24 V		A	2
110 V		A	0.25
Rated frequency	f	Hz	50

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

### Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Pressure switch (EC000243)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Monitoring equipment (low-voltage switch technology) / Pressure monitoring equipment (ecl@ss10.0.1-27-37-18-14 [AKF108014])			
Suitable as guard			Yes
Suitable as 2-point controller			Yes
Suitable as limiter			No
Max. operating pressure	hPa	25000	
Engaging pressure	bar	0 - 21	
Initial setting	hPa	0 - 0	
Switch off pressure	bar	0 - 22	
End setting	hPa	0 - 0	
Pressure-switching differential	bar	0	
Max. test pressure	bar	32	
Bursting pressure	bar	90	
Medium temperature	°C	25 - 80	
Connection			Internal thread cylindrical BSPP-G (ISO 228-1)
Thread size			1/2 inch
Rated voltage Ue at AC 50 Hz	V	0 - 230	
Rated voltage Ue at AC 60 Hz	V	0 - 230	
Rated voltage Ue at DC	V	0 - 110	
Initial value measuring range pressure	Pa	0	

End value measuring range pressure	Pa	0
Rated operation power at AC-3, 400 V	kW	0
Switching capacity at AC-3, 240 V	kA	0
Rated operation current Ie at AC-1, 400 V	A	0
Rated operation current Ie at AC-3, 400 V	A	0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as change-over contact		1
Type of electric connection		Screw connection
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		0
Adjustable current range	A	0 - 0
With hand operation		No
With manual on/off switch		No
Electronic version		No
With display		No
Explosion-proof		No
Degree of protection (IP)		IP65
Degree of protection (NEMA)		Other
Height	mm	111
Width	mm	60
Diameter	mm	0
Depth	mm	96