

Fuse holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 2P, UL, IEC

Part no. **2Pole 30A 600V MFH For 10X38 Midget fuse**
 Catalog No. **CHM2DU**



Delivery program

Product range		Fuse accessory
Basic function		Fuse-holder
Field of application		low voltage
Rated current	I	A
Rated voltage		32
Size		AC 690 V
Description		10 x 38 mm
Number of poles		DIN rail mounting
usable for size/applications		colour-coded
Standard/Approval		Rated for use with 75°C or 90°C wire
Standards/Regulations		fine stranded wire
		spade terminals and with comb-bus bars
		Use any higher temperature rated wire with appropriate derating.
		Modular
Number of poles		2P
usable for size/applications		for cylindrical fuse-links
Standard/Approval		for midget fuses
Standards/Regulations		UL
		IEC
		cULus
		CCC
		CSA
		UR

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)	
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss8.1-27-14-21-21 [ADI305004])	
For fuse size	10x38 mm
Number of poles	2
Concurrently switching N-neutral	No