



Fuse-link, low voltage, 100 A, AC 400 V, 120 kA, NH02, gL/gG, IEC, dual indicator, live gripping lugs

Part no. **NH FUSE 100A 400V GG/GL SIZE 02**  
 Catalog No. **100NHG02B-400**

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	100
Rated voltage			AC 400 V
Construction size			NH02
Utilization category			gL/gG
Status indicator			dual indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Fuse construction type according to IEC 60269			NH02
Voltage type			AC
Rated current		A	100
Rated voltage AC		V	400
Rated voltage DC		V	
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No
Power loss at rated current		W	6.6