



Fuse-link, low voltage, 80 A, AC 690 V, 120 kA, NH00, aM, IEC, dual indicator, live gripping lugs

Part no. **NH FUSE 80A 690V aM SIZE 00**  
 Catalog No. **80NHM00B-690**

EL-Nummer **1664144**  
 (Norway)

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	80
Rated voltage			AC 690 V
Construction size			NH00
Utilization category			aM
Status indicator			dual indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Fuse construction type according to IEC 60269			NH00
Voltage type			AC
Rated current		A	80
Rated voltage AC		V	690
Rated voltage DC		V	
Rated switching capacity		kA	120
Utilization category			aM (switchgear protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No
Power loss at rated current		W	4.3