

## Control circuit terminal, box terminal

Part no. **NZM-XSTK**  
Catalog No. **266739**



## Delivery program

|                            |                 |  |
|----------------------------|-----------------|--|
| Accessories                |                 | Control circuit terminal   |
| For use with               |                 | NZM1(-4), PN1(-4), N(S)1(-4)<br>NZM2(-4), PN2(-4), N(S)2(-4)<br>NZM3(-4), PN3, N(S)3(-4) |
| <b>Terminal capacities</b> |                 |  |
| Type of conductor          |                 | Box terminal   |
| Cu/Al cable                |                 |  |
| Terminal capacities        |                 |  |
| flexible                   | mm <sup>2</sup> | 1 x 0.75 - 2.5<br>2 x 0.75 - 1.5   |
| AWG/kcmil                  | mm <sup>2</sup> | 1 x 18 - 14<br>2 x 18 - 16   |

## Notes

Part contains parts for two terminal locations located at top or bottom for 3 or 4 pole circuit-breakers.

Included as standard with tunnel terminal

Degree of protection IP1X

NZM-XSTK cannot be combined with NZM2(1)-XIPK IP4X protection against contact with a finger.

When using NZM1-XKSA, the plastic cover of the NZM-XSTK must not be fitted.

Height and thickness of control terminals:

NZM-XSTK = 2 mm

NZM-XSTS = 2 mm

## Design verification as per IEC/EN 61439

|  |  |  |
|--|--|--|
| IEC/EN 61439 design verification   |  |  |
| 10.2 Strength of materials and parts   |  |  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures   |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |  | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections  |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |  |  |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Distribution terminal block (EC000276)

Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Control line board (ecl@ss10.0.1-27-14-11-47 [BAA026013])

|                    |                 |     |
|--------------------|-----------------|-----|
| Core cross section | mm <sup>2</sup> | 2.5 |
| Number of poles    |                 | 1   |
| With seal head     |                 | No  |