

## Adapter dla wyłączników NZM 550A UL508

Typ **NZM3-XAD550**  
 Catalog No. **104556**

## Program dostaw

|  |                |    |                  |
|--|----------------|----|------------------|
| Znamionowy prąd pracy  | I <sub>e</sub> | A  | 550              |
| Stosowane do   |                |    | NZM3, PN3, N(S)3 |
| Cu factor  |                | kg | 1,11             |
| <b>Uwagi</b>   |                |    |                  |
| Connection to the system possible at top via connection on rear with (+)NZM3-XK13... |                |    |                  |
| Mounting using clamp and screw fixing.   |                |    |                  |

## Dane techniczne zgodne z ETIM 5.0

|   |  |    |      |
|---|--|----|------|
| Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)  |  |    |      |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecl@ss8-27-37-03-04 [ACN951007]) |  |    |      |
| Mounting rail armament  |  |    | None |
| Type of electrical connection   |  |    | -    |
| Rated current I <sub>n</sub>  |  | A  | 550  |
| Min. busbar thickness   |  | mm | 5    |
| Max. busbar thickness   |  | mm | 10   |
| Width of the adapter  |  | mm | 140  |
| Rail width  |  | mm | 30   |
| Busbar distance   |  | mm | 0    |