

Acoustic device, compact, IP40_x



Part no.	M22-AMC
Catalog No.	229015
Alternate Catalog No.	M22-AMCQ
EL-Nummer (Norway)	4355447

Delivery program

Product range	RMQ-Titan
Basic function	Acoustic device
Single unit/Complete unit	Single unit
Description	without buzzer with BA 9s lamp socket
Colour	Black
Degree of Protection	IP40
Connection to SmartWire-DT	no

Technical data

General			
Standards	IEC/EN 60947 VDE 0660		
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30		
Degree of Protection	IP40		
Ambient temperature			
Open	°C	-25 - +70	
Mounting position	As required		
Mechanical shock resistance	g	30 Shock duration 11 ms Sinusoidal according to IEC 60068-2-27	
Terminal capacities	mm ²		
Solid	mm ²	2 x (0.5 - 1.5)	
Stranded	mm ²	0.5 - 1.5	
Shipping classification	DNV GL LR		

Contacts

Rated impulse withstand voltage	U _{imp}	V AC	4000
Rated insulation voltage	U _i	V	250
Overvoltage category/pollution degree			III/3

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-25	
Operating ambient temperature max.	°C	70	

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Acoustic indicator (EC001026)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Acoustic alarm unit (ecl@ss10.0.1-27-37-12-14 [AKF032014])			
Type of acoustic signal	Continuous tone		
Loudness	dB	0	
Operating voltage at AC 50 Hz	V	0 - 0	
Operating voltage at AC 60 Hz	V	0 - 0	
Operating voltage at DC	V	0 - 0	

Voltage type		AC/DC
Degree of protection (NEMA)		4X, 13