

PRODUCT-DETAILS

OVR T2-T3 20-440 P TS QS

OVR T2-T3 20-440 P TS QS Surge Protective Device



General Information

Extended Product Type	OVR T2-T3 20-440 P TS QS
Product ID	2CTB803871R1300
EAN	3660308519610
Catalog Description	OVR T2-T3 20-440 P TS QS Surge Protective Device
Long Description	OVR T2-T3 20-440 P TS QS Surge Protective Device

Technical

Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TT TN-C TN-S IT
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U_r)	690 V AC
Nominal AC Voltage of the System (U_o)	400 / 690 V
Voltage Rating DC	560 V
Voltage Protection Level (U_p)	1.4 kV (L-N) 1.8 kV
Maximum Continuous Operating Voltage (U_c)	(L-PE) 440 V
Temporary Overvoltage Test Value (U_T)	581 V

Rated Service Short-Circuit Breaking Capacity (I_{cs})	100 kA
Discharge Current	Nominal (8 / 20 μ s) 5 kA I (max, 8 / 20 μ s) 5 kA
Impulse Current	I (imp, 10 / 350 μ s) 2 kA
Short Circuit Withstand Icc	100 kA
Arrester Class	II III
Number of Protected Poles	1
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Poles	1
Number of Conductors	1
Transmission Standard	Optic
Version	Plug-in
Mounting Type	DIN-Rail
Product Type	QS
Options Provided	Residential or other where accurate protection is needed.
Auxiliary Circuit Load	Minimum 12Vdc - 10mA Maximum 250Vac - 1A
Preventive Maintenance Feature	No
Status Indicator	Yes
Fuse Size	1 modular spacing

Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000
RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	9AKK108466A4410
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	17.8 mm
Product Net Height	95 mm
Product Net Depth / Length	58 mm
Product Net Weight	0.12 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	145 g

Certificates and Declarations

CB Certificate	2CTC432057G1701
CQC Certificate	9AKK107680A1974

Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4410
EAC Certificate	2CTC436007G1701

Installation

Instructions and Manuals	2CTC432097M1701
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CTC432211D0201
Mechanical Drawings	2CTC800021F0200.pdf 2CTC800021F0201.dxf 2CTC800021F0202.stp 2CTC800021F0203.igs

Classifications

ETIM 8	EC000941 - Surge protection device for power supply systems
ETIM 9	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363090
eClass	V11.0 : 27130805
Object Classification Code	141EEC

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II → Type T2 - T3 20kA

