

**Motor-protective circuit-breaker, Complete device with standard knob,  
Electronic, 8 - 32 A, With overload release, Screw terminals**

**Part no.** PKE32/XTU-32  
**Catalog No.** 121734  
**Alternate Catalog No.** XTPE032BCSNL  
**EL-Nummer (Norway)** 4355183

## Delivery program

Product range	PKE motor protective circuit-breakers with electronic wide-range overload protection up to 32 A			
Basic function	Motor protection Motor protection for heavy starting duty			
Single unit/Complete unit	Complete device with standard knob			
Notes	Also suitable for motors with efficiency class IE3.			
Connection technique	Screw terminals			
Setting range of overload releases	I <sub>r</sub>	A	8 - 32	
				
Function	With overload release			
Rated uninterrupted current = rated operational current	I <sub>u</sub> = I <sub>e</sub>	A	32	
<b>Motor rating</b>				
AC-3				
220 V 230 V 240 V	P	kW	7.5	
380 V 400 V 415 V	P	kW	15	
440 V	P	kW	15	
500 V	P	kW	18.5	
660 V 690 V	P	kW	30	
Motor output/rated motor current				
Motor rating	Rated motor current			
AC-3				
220 V	380 V	440 V	500 V	660 V
230 V	400 V			690 V
240 V	415 V			
P	I	I	I	I
kW	A	A	A	A
2.2	8.7	-	-	-
3	11.5	-	-	-
4	14.8	8.5	-	-
5.5	19.6	11.3	10.2	9
7.5	26.4	15.2	13.8	12.1
11	-	21.7	19.8	17.4
15	-	29.3	26.6	23.4
18.5	-	-	-	17
22	-	-	-	20.9
30	-	-	-	23.8
			-	32

## Technical data

General			
Standards		IEC/EN 60947, VDE 0660, UL, CSA	
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30	
Ambient temperature			
Storage	°C	- 40 - 80	
Open	°C	- 25 - +55	
Enclosed	°C	- 25 - 40	
Direction of incoming supply		as required	
Degree of protection		IP20	
Device		IP00	
Terminations			

Protection against direct contact when actuated from front (EN 50274)			Finger and back-of-hand proof
Mechanical shock resistance half-sinusoidal shock 10 ms to IEC 60068-2-27	g	25	
Altitude	m	Max. 2000	
Terminal capacity main cable			
Screw terminals			
Solid	mm <sup>2</sup>	1 x (1 - 6) 2 x (1 - 6)	
Flexible with ferrule to DIN 46228	mm <sup>2</sup>	1 x (1 - 6) 2 x (1 - 6)	
Solid or stranded	AWG	14 - 10	
Stripping length	mm	10	
Specified tightening torque for terminal screws			
Main cable	Nm	1.7	
Control circuit cables	Nm	1	

### Main conducting paths

Rated impulse withstand voltage	U <sub>imp</sub>	V AC	6000
Overvoltage category/pollution degree			III/3
Rated operational voltage	U <sub>e</sub>	V AC	690
Rated uninterrupted current = rated operational current	I <sub>u</sub> = I <sub>e</sub>	A	32
Rated frequency	f	Hz	50/60
Current heat loss (3 pole at operating temperature)		W	11.4
Lifespan, mechanical	Operations	x 10 <sup>6</sup>	0.05
Lifespan, electrical (AC-3 at 400 V)			
Lifespan, electrical	Operations	x 10 <sup>6</sup>	0.05
Max. operating frequency		Ops/h	60
Motor switching capacity			
AC-3 (up to 690V)	A		32
AC-4 cycle operation			
Minimum current flow times		ms	500 (Class 5) 700 (Class 10) 900 (Class 15) 1000 (Class 20)
Minimum cut-out periods		ms	500
Note		ms	In AC-4 cycle operation, going below the minimum current flow time can cause overheating of the load (motor). For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

### Trip blocks

Temperature compensation			
to IEC/EN 60947, VDE 0660		°C	- 5 ... 40
Operating range		°C	- 25 ... 55
Setting range of overload releases		x I <sub>u</sub>	0.25 - 1
short-circuit release			Basic device, fixed: 15.5 x I <sub>u</sub> Trip block, fixed: 15.5 x I <sub>u</sub> delayed approx. 60 ms
Short-circuit release tolerance			± 20%
Phase-failure sensitivity			IEC/EN 60947-4-1, VDE 0660 Part 102

### Rating data for approved types

Switching capacity			
Maximum motor rating			
Three-phase			
200 V 208 V	HP	5	
230 V 240 V	HP	7.5	
460 V 480 V	HP	15	
575 V 600 V	HP	20	
Single-phase			
115 V	HP	1.5	

120 V			
230 V			
240 V			
General use		A	32
Short Circuit Current Rating, group protection		SCCR	
600 V High Fault			
SCCR (fuse)		kA	100
max. Fuse		A	100 Class J

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	32
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	3.8
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	11.4
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss10.0.1-27-37-04-01 [AGZ529016])			
Overload release current setting	A	32 - 32	
Adjustment range undelayed short-circuit release	A	496 - 496	
With thermal protection		No	
Phase failure sensitive		No	
Switch off technique		Electronic	
Rated operating voltage	V	690 - 690	

Rated permanent current I <sub>u</sub>	A	32
Rated operation power at AC-3, 230 V	kW	7.5
Rated operation power at AC-3, 400 V	kW	15
Type of electrical connection of main circuit		Screw connection
Type of control element		Turn button
Device construction		Built-in device fixed built-in technique
With integrated auxiliary switch		No
With integrated under voltage release		No
Number of poles		3
Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, AC	kA	100
Degree of protection (IP)		IP20
Height	mm	102.5
Width	mm	45
Depth	mm	101